

DIN rail adapter - DR 35-PC 35 - 1708409

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail adapter, for snapping the PC 35/IPC 35 connector onto a DIN rail, color: green, mounting type: NS 35/7,5, NS 35/15



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 046356 998291
GTIN	4046356998291
Weight per Piece (excluding packing)	18.000 g
Custom tariff number	85389099
Country of origin	China

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.0	27370400
eCl@ss 5.1	27370400
eCl@ss 6.0	27370400
eCl@ss 7.0	27370419

DIN rail adapter - DR 35-PC 35 - 1708409

Classifications

eCl@ss

eCl@ss 8.0	27370419
eCl@ss 9.0	27370419

ETIM

ETIM 5.0	EC001024
ETIM 6.0	EC001024
ETIM 7.0	EC001024

UNSPSC

UNSPSC 13.2	39121708
-------------	----------

Accessories

Additional products

Printed-circuit board connector - IPC 35 HC/ 2-STGF-15,00 - 1784855



PCB connector, nominal current: 125 A, number of positions: 2, pitch: 15 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Silver

Printed-circuit board connector - IPC 35 HC/ 3-STGF-15,00 - 1784868



PCB connector, nominal current: 125 A, number of positions: 3, pitch: 15 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Silver

Printed-circuit board connector - IPC 35 HC/ 4-STGF-15,00 - 1784871



PCB connector, nominal current: 125 A, number of positions: 4, pitch: 15 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Silver

DIN rail adapter - DR 35-PC 35 - 1708409

Accessories

Printed-circuit board connector - IPC 35 HC/ 5-STGF-15,00 - 1784884



PCB connector, nominal current: 125 A, number of positions: 5, pitch: 15 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Silver

Printed-circuit board connector - IPC 35 HC/ 6-STGF-15,00 - 1784897



PCB connector, nominal current: 125 A, number of positions: 6, pitch: 15 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Silver
