

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1714461102](#)
Status: **Active**
Overview: [SpeedStack™ Mezzanine Connector System](#)
Description: SpeedStack Vertical Plug, 0.80mm Pitch, 1.90mm Height, 22 Circuits, UL94V-0, Black

Documents:

[3D Model](#) [Packaging Specification PK-70873-6003 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[3D Model \(PDF\)](#)

General

Product Family PCB Headers
Series [171446](#)
Application Board-to-Board
Overview [SpeedStack™ Mezzanine Connector System](#)
Product Name SpeedStack
UPC 889056432726

Physical

Breakaway No
Circuits (Loaded) 22
Circuits (maximum) 22
Color - Resin Black
Durability (mating cycles max) 20
Glow-Wire Capable No
Material - Metal Copper Alloy
Material - Plating Mating Gold
Material - Plating Termination Matte Tin
Material - Resin Liquid Crystal Polymer
Net Weight 0.200/g
Number of Rows 2
Orientation Vertical
Packaging Type Embossed Tape on Reel
Pitch - Mating Interface 0.80mm
Pitch - Termination Interface 0.80mm
Plating min - Mating 0.762µm
Plating min - Termination 0.762µm
Surface Mount Compatible (SMC) Yes
Temperature Range - Operating -40° to +105°C
Termination Interface: Style Surface Mount


Electrical

Current - Maximum per Contact 0.8A
Voltage - Maximum 5V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Packaging Specification PK-70873-6003
Sales Drawing SD-171446-1000-001



EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2020)4578-DC (25
June 2020)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[171446 Series](#)

Mates With

SpeedStack Vertical Receptacle [171450](#)