

**PLUG HSG ASSY 2P&3P SEALED JPT PLUG CONNECTOR**

**1. PURPOSE 目的**

Define the packaging specification and packaging method of PLUG HSG ASSY 2P&3P SEALED JPT PLUG CONNECTOR.

訂定 PLUG HSG ASSY 2P&3P SEALED JPT PLUG CONNECTOR 产品之包装规格及包装方式。

**2. APPLICABLE PRODUCT 适用范围**

Product Part Number	Description
1717696-X	PLUG HSG ASSY 3POSN SEALED JPT PLUG CONNECTOR
1717692-X	PLUG HSG ASSY 2POSN SEALED JPT PLUG CONNECTOR

**3. PACKAGING MATERIAL 包装材料**

Package	Part No.	Description	Usage	
			1717696-X	1717692-X
INNER	995265-5	BAG, GUSSETEDM ANTISTATIC, SPECIAL	1/800	1/1000
	110455-2	BUBBLE PACK	4/800	4/1000
	623865-4	INNER LABEL	1/800	1/1000
MIDDLE	-	-	-	-
OUTER	115216	SHIPPING BOX	1/800	1/1000
	623865-1	OUTER LABEL	1/800	1/1000

	Inner	Middle	Outer
LABEL	623865-4	-	623865-1
SEALING	Tie	-	Tape

**4. PACKAGING QUANTITY 包装数量**

	Inner	Middle	Outer
1717696-X	800 pcs/bag	-	800 pcs/box
1717692-X	1000 pcs/bag	-	1000 pcs/box

DR <b>Liu Haifeng</b>	CHK <b>Harvy Wang</b>	APVD <b>Michelle Peng</b>
--------------------------	--------------------------	------------------------------

## 5. PACKING METHOD 包装方法

5.1. Set up a box & secure bottom flaps with tape.

折叠好一个包装箱，并用胶带封好箱底。

5.2. Place two pieces of bubble pack with bubble facing down into bottom of the box.

在箱底放入二块气泡垫，气泡面朝下。

5.3. Open the polybag & into the shipping box.

打开一个塑料袋并放入外箱中。

Only for 1717696-X:

5.4.1. Weight or count 800 parts into bag.

称重或数数800个产品放入袋中。

Only for 1717692-X:

5.4.2. Weight or count 1000 parts into bag.

称重或数数1000个产品放入袋中。

5.5. Tie placket of bag with wire tie.

用黑色扎带捆扎袋口。

5.6. Place an inner label on the proper position of polybag.

在塑料袋的适当位置贴上内标签(保证开箱者开箱后对内标签一目了然)。

5.7. Place two pieces of bubble pack on top of the products, and bubble facing up.

最后在上面放二块气泡垫，气泡面朝上。

5.8. Seal the box with tape. And place product identification label in "product id" marked on box.

用胶带封箱，在箱外印有“PRODUCT ID”标识处贴上外标签。