

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [171814-4010](#)
Status: **Active**
Overview: [KK® Interconnect System - Molex](#)
Description: [KK® 396 RPC Wire-to-Board Right Angle Header with Friction Lock, 10 Circuits, 15µm Gold \(Au\)](#)

Documents:

| | |
|--|--|
| 3D Model | Test Summary TS-171813-0001 (PDF) |
| Drawing (PDF) | Test Summary TS-171814-0001 (PDF) |
| Product Specification PS-171813-0001 (PDF) | RoHS Certificate of Compliance (PDF) |
| Product Specification PS-171813-0002 (PDF) | |



image - Reference only

General

| | |
|----------------|---|
| Product Family | PCB Headers |
| Series | 171814 |
| Application | Power, Signal, Wire-to-Board |
| Overview | KK® Interconnect System - Molex |
| Product Name | KK® 396 |
| UPC | 887191718408 |

Physical

| | |
|--------------------------------|--------------------------------|
| Breakaway | No |
| Circuits (Loaded) | 10 |
| Circuits (maximum) | 10 |
| Color - Resin | Black |
| Durability (mating cycles max) | 25 |
| First Mate / Last Break | No |
| Glow-Wire Compliant | Yes |
| Guide to Mating Part | No |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Material - Metal | Brass |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Nickel |
| Material - Resin | High Temperature Thermoplastic |
| Net Weight | 4.230/g |
| Number of Rows | 1 |
| Orientation | Right Angle |
| PCB Locator | No |
| PCB Retention | None |
| PCB Thickness - Recommended | 1.60mm |
| Packaging Type | Embossed Tape on Reel |
| Pitch - Mating Interface | 3.96mm |
| Plating min - Mating | 0.381µm |
| Polarized to Mating Part | Yes |
| Shrouded | Partial |
| Stackable | No |
| Surface Mount Compatible (SMC) | Yes |
| Temperature Range - Operating | -40°C to +105°C |
| Termination Interface: Style | Through Hole |

Electrical

| | |
|-------------------------------|------|
| Current - Maximum per Contact | 13A |
| Voltage - Maximum | 600V |

Solder Process Data

EU RoHS

ELV and RoHS Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[171814Series](#)

Mates With

[2145](#) , [41815](#) , [6442](#) , [2139](#) , [41714](#)

| | |
|--|------------------------------|
| Duration at Max. Process Temperature (seconds) | 30 |
| Lead-free Process Capability | SMC & Wave Capable (TH only) |
| Max. Cycles at Max. Process Temperature | 3 |
| Process Temperature max. C | 260 |

Material Info

Reference - Drawing Numbers

| | |
|-----------------------|--------------------------------|
| Product Specification | PS-171813-0001, PS-171813-0002 |
| Sales Drawing | SD-171814-0001 |
| Test Summary | TS-171813-0001, TS-171814-0001 |

This document was generated on 07/21/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION