

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1719740213](#)  
**Status:** **Active**  
**Overview:** [SL Modular Connectors](#)  
**Description:** 2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 13 Circuits

**Documents:**

[3D Model](#) [Product Specification 1719710000-PS-000 \(PDF\)](#)  
[3D Model \(PDF\)](#) [Packaging Specification 1719740000-PK-000 \(PDF\)](#)  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**General**

Product Family PCB Headers  
Series [171974](#)  
Application Signal, Wire-to-Board  
Overview [SL Modular Connectors](#)  
Product Name SL  
UPC 191128197106

**Physical**


Breakaway No  
Circuits (Loaded) 13  
Circuits (maximum) 13  
Color - Resin Black  
First Mate / Last Break No  
Glow-Wire Capable No  
Guide to Mating Part No  
Keying to Mating Part None  
Lock to Mating Part Yes  
Material - Metal Brass  
Material - Plating Mating Gold  
Material - Plating Termination Matte Tin  
Material - Resin Liquid Crystal Polymer  
Net Weight 2.859/g  
Number of Rows 1  
Orientation Right Angle  
PC Tail Length 3.30mm  
PCB Locator No  
PCB Retention None  
PCB Thickness - Recommended 1.57mm  
Packaging Type Tube  
Pitch - Mating Interface 2.54mm  
Pitch - Termination Interface 2.54mm  
Plating min - Mating 0.750µm  
Plating min - Termination 2.000µm  
Polarized to Mating Part Yes  
Polarized to PCB Yes  
Shrouded Fully  
Temperature Range - Operating -40° to +105°C  
Termination Interface: Style Through Hole

**Electrical**

Current - Maximum per Contact 3.0A  
Voltage - Maximum 250V

**Material Info**

**Reference - Drawing Numbers**



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

For more information, please visit [Contact US](#)

China ROHS

Not Reviewed

ELV

Not Relevant

RoHS Phthalates

Not Reviewed

**China RoHS**

**Search Parts in this Series**

[171974 Series](#)

**Mates With**

SL Insulation Displacement Connector Assembly [70400](#) (Version G) <br>SL Receptacle [70430](#) (Version G), [70066](#) (Version G and N)

Packaging Specification  
Product Specification  
Sales Drawing

1719740000-PK-000  
1719710000-PS-000  
1719740000-SD-000

This document was generated on 06/04/2020

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**