



Shielded No  
Voltage - Maximum 30V AC (RMS)/DC

**Solder Process Data**

Duration at Max. Process Temperature (seconds) 020  
Lead-free Process Capability REFLOW  
Max. Cycles at Max. Process Temperature 001  
Process Temperature max. C 260

**Material Info**

benzo[ghi]perylene  
ethylene thiourea  
phenanthrene  
[phthalato(2-)]dioxotrilead  
Silicic acid (H<sub>2</sub>Si<sub>2</sub>O<sub>5</sub>),  
barium salt (1:1),  
lead-  
Sulfurous acid, lead  
salt, dibasic  
cadmium hydroxide  
pyrochlore, antimony  
lead yellow  
orange lead  
1,2-bis(2-  
methoxyethoxy)ethane  
1,2-dimethoxyethane  
bis(2-methoxyethyl)  
phthalate  
pentazinc chromate  
octahydroxide  
tetraboron disodium  
heptaoxide, hydrate  
tris(2-chloroethyl)  
phosphate

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

**Search Parts in this Series**

[171983](#) Series

This document was generated on 10/16/2020

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**