

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [172064-0012](#)
Status: **Active**
Overview: Mega-Fit Power Connectors
Description: Mega-Fit™ Right-Angle Header, 12 Circuits, 15µ" Gold (Au) Plating, UL 94 V-0, Tray

Documents:

[3D Model](#) [Test Summary TS-76825-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Product Specification PS-76823-100 \(PDF\)](#)

Agency Certification


CSA LR19980
 UL E29179

General

Product Family PCB Headers
 Series [172064](#)
 Application Power, Wire-to-Board
 Overview [Mega-Fit Power Connectors](#)
 Product Name Mega-Fit™
 UPC 887191453910

Physical

Breakaway No
 Circuits (Loaded) 12
 Circuits (maximum) 12
 Color - Resin Black
 First Mate / Last Break No
 Flammability 94V-0
 Glow-Wire Compliant Yes
 Keying to Mating Part Yes
 Lock to Mating Part Yes
 Mated Height 16.78mm
 Material - Metal Copper
 Material - Plating Mating Nickel
 Material - Plating Termination Gold
 Material - Resin High Temperature Thermoplastic
 Net Weight 7.883/g
 Number of Rows 2
 Orientation Right Angle
 PCB Locator Yes
 PCB Retention Yes
 PCB Thickness - Recommended 1.57mm, 2.36mm
 Packaging Type Tray
 Pitch - Mating Interface 5.70mm
 Pitch - Termination Interface 5.70mm
 Plating min - Mating 0.381µm
 Plating min - Termination 1.270µm
 Polarized to Mating Part Yes
 Polarized to PCB Yes
 Shrouded Yes
 Surface Mount Compatible (SMC) Yes
 Temperature Range - Operating -40°C to +105°C
 Termination Interface: Style Through Hole
 Unmated Height 14.53mm



Series

image - Reference only

EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

**Contains SVHC: No
Low-Halogen Status
Low-Halogen**

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[172064Series](#)

Mates With

Mega-Fit™ Receptacle Housing [171692](#) ,
[170001](#)

Electrical

Current - Maximum per Contact	23A
Voltage - Maximum	600V

Solder Process Data

Duration at Max. Process Temperature (seconds)	30
Lead-free Process Capability	SMC & Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	260

Material Info**Reference - Drawing Numbers**

Product Specification	PS-76823-100
Sales Drawing	SD-76825-0100
Test Summary	TS-76825-001

This document was generated on 01/07/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION