

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1731130214](#)  
**Status:** **Active**  
**Overview:** [FCT D-Sub Connectors](#)  
**Description:** FCT High-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 5.60mm Snap-in Bolt, 15 Circuits

**Documents:**

[Brochure \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**General**

|                  |                                      |
|------------------|--------------------------------------|
| Product Family   | D-Sub Products                       |
| Series           | <a href="#">173113</a>               |
| IP Rating        | IP20                                 |
| Overview         | <a href="#">FCT D-Sub Connectors</a> |
| Product Category | D-Sub Connector                      |
| Product Name     | FCT Products                         |
| Type             | High Density                         |
| UPC              | 191128954945                         |

**Physical**


|                                |                  |
|--------------------------------|------------------|
| Circuits (Loaded)              | 15               |
| Circuits (maximum)             | 15               |
| Color - Resin                  | Black            |
| Durability (mating cycles max) | 50               |
| Gender                         | Male             |
| Material - Contact             | Copper Alloy     |
| Material - Resin               | PBT              |
| Material - Shell               | Steel            |
| Net Weight                     | 6.200/g          |
| Number of Rows                 | 3                |
| Orientation                    | Straight         |
| PC Tail Length                 | 9.50mm           |
| PCB Locator                    | Yes              |
| PCB Retention                  | Yes              |
| PCB Thickness - Recommended    | 1.60mm           |
| Packaging Type                 | Carton           |
| Panel Mount                    | Rear             |
| Panel Mount Method             | Thread-In        |
| Pitch - Mating Interface       | 1.98mm           |
| Pitch - Termination Interface  | 1.98mm           |
| Plating - Contact              | Gold over Nickel |
| Plating - Shell                | Tin              |
| Polarized to Mating Part       | Yes              |
| Polarized to PCB               | Yes              |
| Ports                          | 1                |
| Shielded                       | Yes              |
| Temperature Range - Operating  | -55° to +105°C   |
| Termination Style              | Through Hole     |
| Waterproof / Dustproof         | No               |
| Waterproof / Dustproof Type    | IP20             |

**Electrical**

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 3.0A |
|-------------------------------|------|

**Material Info**

|                    |                |
|--------------------|----------------|
| Engineering Number | CT09-15P1-0981 |
|--------------------|----------------|



**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant with Exemption 6(c)**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

For more information, please visit [Contact US](#)

China ROHS

50 Image

ELV

Not Relevant

RoHS Phthalates

Not Contained

**Search Parts in this Series**

[173113 Series](#)

**Mates With**

FCT High-Density D-Sub, Size 1, 15 Position, Socket

This document was generated on 05/27/2020

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**