

ADAP EX M63-M50

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Similar to illustration



ADAP series adaptors provide flexibility and versatility infilling unused entries in Ex equipment while maintaining Flameproof Ex d and Increased Safety Ex e explosion protection and IP66/67/68 ingress rate.

General ordering data

Version	ADAP (adaptor, extensions and reductions), Adapter, M 63 ,M 50, IP54, Brass, nickel-plated
Order No.	1738190000
Type	ADAP EX M63-M50
GTIN (EAN)	4008190958084
Qty.	1 pc(s).

ADAP EX M63-M50

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight 281 g

Temperatures

Operating temperature -40 °C...100 °C

Operating temperature, min. -40 °C

Operating temperature, max. 100 °C

Certificate numbers cable gland

Approval conditions ATEX, IECEX

Certificate no. cable gland (ATEX) SIRA 10ATEX1225X

Certificate no. cable gland (IECEX) IECEX SIR 07.0010X

Identification II 2 GD, Ex d IIC, Ex e II, Ex tD

General information

Cable glands metric

External thread M 63

Internal thread M 50

Material Brass, nickel-plated

Note: protection class Please follow the operating instructions to attain higher IP protection.

Operating temperature range, max.

100 °C

Operating temperature range, min. -40 °C

Pitch of thread 1.5 mm

Protection degree IP54

Protection degree with GWDR IP54

Classifications

ETIM 6.0 EC000441

ETIM 7.0 EC000441

ETIM 8.0 EC000441

ECLASS 9.0 27-14-44-32

ECLASS 9.1 27-14-44-90

ECLASS 10.0 27-14-44-32

ECLASS 11.0 27-14-44-32

ECLASS 12.0 27-14-08-06

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

SCIP 69c399a3-d29f-4fa4-b22e-340c0db02257

Approvals

Approvals



ROHS Conform

DownloadsEngineering Data [WSCAD](#)Catalogues [Catalogues in PDF-format](#)