

Header - STB 3/4-G-5,08 - 1751044

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB headers, number of positions: 4, pitch: 5.08 mm, color: green, contact surface: Tin, Pin layout: Linear double pinning, solder pin [P]: 5.1 mm



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 028312
GTIN	4017918028312
Weight per Piece (excluding packing)	2.820 g
Custom tariff number	85366930
Country of origin	Poland

Technical data

Dimensions

Length [l]	14.8 mm
Width	25.36 mm
Pitch	5.08 mm
Dimension a	15.24 mm
Width [w]	25.36 mm
Height [h]	21.1 mm
Height	16 mm
Length of the solder pin	5.1 mm
Pin spacing	5.08 mm
Length	14.8 mm

General

Range of articles	STB
Color	green
Stripping length	8 mm
Number of positions	4

Header - STB 3/4-G-5,08 - 1751044

Technical data

Standards and Regulations

Connection in acc. with standard	CSA
----------------------------------	-----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002498
ETIM 5.0	EC002637
ETIM 6.0	EC002637
ETIM 7.0	EC002637

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409
UNSPSC 18.0	39121409
UNSPSC 19.0	39121409
UNSPSC 20.0	39121409
UNSPSC 21.0	39121409

Approvals

Approvals

Header - STB 3/4-G-5,08 - 1751044


Approvals


Approvals

CSA / UL Recognized / EAC

Ex Approvals

Approval details

CSA		http://www.csagroup.org/services-industries/product-listing/	13631
Nominal voltage UN		300 V	
Nominal current IN		10 A	

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 60425
Nominal voltage UN		300 V	
Nominal current IN		10 A	

EAC			B.01742
-----	---	--	---------
