

1801174-4 ✓ ACTIVE

### Sensor Flat Contact System

TE Internal #: 1801174-4

Housing for Male Terminals, Wire-to-Wire, 2 Position, .131 in [3.33 mm] Centerline, Sealable, Yellow, Wire & Cable, Signal, Sensor Flat Contact System

[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Housings



Connector System: **Wire-to-Wire**

Number of Positions: **2**

Connector & Housing Type: **Housing for Male Terminals**

Centerline (Pitch): **3.33 mm [ .131 in ]**

Sealable: **Yes**

## Features

### Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal

### Configuration Features

Number of Positions	2
Number of Rows	1

### Electrical Characteristics

Operating Voltage	16 VDC
Nominal Voltage Architecture	16 V

### Body Features

Cable Exit Angle	180°
Primary Product Color	Yellow
Connector & Keying Code	4

### Contact Features



Contact Size	1.5mm
Contact Type	Tab
Contact Current Rating (Max)	8 A

#### Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

#### Housing Features

Housing Material	PBT GF
Centerline (Pitch)	3.33 mm[.131 in]

#### Dimensions

Connector Height	17.6 mm[.693 in]
Product Width	55.8 mm[2.197 in]
Product Length	17.4 mm[.685 in]

#### Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C, 140 °C, 145 °C, 150 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F][284 °F][293 °F][302 °F]
Operating Temperature Range	-40 – 150 °C[-40 – 302 °F]

#### Operation/Application

Circuit Application	Signal
---------------------	--------

#### Industry Standards

Degree of Protection	IP69K
UL Flammability Rating	UL 94HB

#### Other

Serviceable	Yes
Connector Position Assurance Capable	No

#### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



TE Part # CAT-AM706-T273  
AMP MCP, SFC, RECEPTACLE



TE Part # 1801155-5  
COVER FOR 2W HP CONNECTOR



TE Part # 1-1579008-3  
EXTRACTION TOOL



TE Part # 1-1579008-1  
EXTRACTION TOOL SECONDARY LOCK OPENING



TE Part # 1-1579008-4  
EXTRACTION TOOL, 2POS. SECONDARY LOCK CL.



TE Part # 1-1801155-5  
COVER FOR 2W HP CONNECTOR







TE Part # 1-1801175-4  
2W RECEPTACLE HP CONNECTOR YELLOW




TE Part # 1-1801175-9  
2W RECEPTACLE HP CONNECTOR ORANGE



Also in the Series | **Sensor Flat Contact System**



Customers Also Bought





## Documents

### Product Drawings

#### 2W TAB HP CONNECTOR YELLOW

English

### CAD Files

#### Customer View Model

[ENG\\_CVM\\_CVM\\_1801174-4\\_B.2d\\_dxf.zip](#)

English

#### 3D PDF

3D

#### Customer View Model

[ENG\\_CVM\\_CVM\\_1801174-4\\_B.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_1801174-4\\_B.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Product Specifications

#### Product Specification

English