

**Cabtite**  
**CABTITE KT 24 b****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

**General ordering data**

|            |   |
|------------|---|
| Type       | CABTITE KT 24 b   |
| Order No.  | <a href="#">1828030000</a>  |
| Version    | Cable grommet, large design, Cabtite, Plastic, Black, Height: 42 mm, Width: 41.5 mm, Depth: 19 mm, 24.00 - 25.00 mm, -20 °C - 80 °C |
| GTIN (EAN) | 4032248333547   |
| Qty.       | 10 pc(s).   |

## Data sheet

### Cabtite CABTITE KT 24 b

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 41.5 mm | Width (inches)  | 1.634 inch |
| Height     | 42 mm   | Height (inches) | 1.654 inch |
| Depth      | 19 mm   | Depth (inches)  | 0.748 inch |
| Net weight | 22.8 g  |                 |            |

### General information

|                                   |         |                                   |       |
|-----------------------------------|---------|-----------------------------------|-------|
| Material                          | Plastic | Operating temperature range, max. | 80 °C |
| Operating temperature range, min. | -20 °C  | Outer cable diameter, max.        | 25 mm |
| Outer cable diameter, min.        | 24 mm   |                                   |       |

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000879    | ETIM 4.0   | EC000441    |
| ETIM 5.0   | EC000441    | ETIM 6.0   | EC000879    |
| UNSPSC     | 30-21-18-01 | eClass 5.1 | 27-14-92-01 |
| eClass 6.2 | 27-14-92-01 | eClass 7.1 | 27-14-92-01 |
| eClass 8.1 | 27-14-92-01 | eClass 9.0 | 27-14-44-38 |
| eClass 9.1 | 27-14-44-21 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                     |
|--------------------|-------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 5 ENCL 17/18 EN</a> |
| Engineering Data   | <a href="#">EPLAN, WSCAD</a>        |