

Housing - VC-MP-K1 - 1884568

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling housing, made of metal, powder-coated type 1, number of modules 2, cable screw connection Pg16

Product Features

- Space-saving PE connection to metal housing
- Any position can be a PE contact



Key commercial data

Packing unit	1 pc
GTIN	 4 017918 164591
Weight per Piece (excluding packing)	385.2 GRM
Custom tariff number	85389099
Country of origin	Poland

Technical data

Dimensions

Height	49 mm
--------	-------

Ambient conditions

Degree of protection	IP65/IP66/IP67
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	When using fiber optics, the bending radii of the cable manufacturers must be observed.
Type	VC1
Degree of protection	IP65/IP66/IP67

Housing - VC-MP-K1 - 1884568

Technical data

General

Locking type	Screw locking
Type of the screw connection	1x Pg16
Pg screw connection	none
Cable exit	Lateral
Number of module slots	2
Housing material	Zinc die-cast
Housing surface material	Powder coating
Ambient temperature (operation)	-40 °C ... 125 °C

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27371205
eCl@ss 5.1	27371205
eCl@ss 6.0	27371205
eCl@ss 7.0	27371205
eCl@ss 8.0	27440202

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Approvals

Approvals

Housing - VC-MP-K1 - 1884568

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details



Drawings

Housing - VC-MP-K1 - 1884568

Dimensioned drawing

