

## Han-Modular Twin hood side entry M25



Image is for illustration purposes only. Please refer to product description.

Part number	19 14 002 0501
Specification	Han-Modular Twin hood side entry M25
HARTING eCatalogue	<a href="https://b2b.harting.com/19140020501">https://b2b.harting.com/19140020501</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Modular® Twin
Type of hood/housing	Hood

### Version

Locking type	Single locking lever
Size	Modular Twin
Version	Side entry
Cable entry	1x M25
Details	Rated voltage $\leq 630$ V Rated impulse voltage $\leq 6$ kV Pollution degree 3 For a complete connector the specified voltage rating is the maximum level which can be achieved. In cases where the used module(s) do offer lower voltage ratings, then these lower ratings are valid. Higher voltage ratings in individual applications can be approved in coordination with HARTING.

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)



Pushing Performance

## Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Specifications	IEC 61984
CE	Yes

## Commercial data

Packaging size	1
Net weight	54.6 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors