





	10		9		8		7		6		5		4		3		2		19160	
	MATERIAL NUMBER	ENGINEERING NUMBER	COLOR	WIRE RANGE	WIRE RANGE MIN.	WIRE RANGE MAX.		VOLTAGE MAX.	DIM A	DIM B	DIM C	DIM D	DIM E							
F	191600039	TL-G	GREY	22-14	2#22	1#14 & 1#20		300	.15/3.8	.26/6.6	.34/8.6	.23/5.8	.60/15.2							
	191600040	TL-B	BLUE	22-14	2#22	3#16		300	.16/4.1	.28/7.1	.39/9.9	.23/5.8	.69/17.5							
	191600041	TL-O	ORANGE	22-14	1#18 & 1#20	4#16 & 1#20		600*	.20/5.1	.39/9.9	.48/12.2	.31/7.9	.87/22.1							
	191600042	TL-Y	YELLOW	22-10	3#20	1#10 & 2#14 & 1#16		600*	.24/6.1	.44/11.2	.55/13.97	.31/7.9	.95/24.1							
	191600043	TL-R	RED	22-8	3#18	3#10		600*	.30/7.6	.51/12.9	.65/16.5	.36/9.1	1.04/26.4							
																			F	



SECTION D-D
SCALE 2:1

REF NOTES:

- 1.) WORKING TEMP. 105°C
- 2.) HOUSING MATERIAL: UL 94V-2
FLAME RETARDANT THERMOPLASTIC
- 3.) * = 1000V MAX. IN LIGHTING FIXTURES AND SIGNS.
- 4.) MOLEX UL FILE NO.: E32244
- 5.) MOLEX CSA FILE NO.: 700095



EC NO: B	DRWN: ASAYDEH 2005/11/03 CHKD: RDEROSS 2005/11/15 APPR: RDEROSS 2005/11/21	QUALITY SYMBOLS DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± .02 1 PLACE ± 0.5 ± --- ANGULAR ± 1 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SCALE 1:1 DESIGN UNITS INCH DIMENSION STYLE IN/MM DRAWN BY B.RUPERT DATE 11/07/03 CHECKED BY J.PAWLIC DATE 11/08/03 APPROVED BY R.DEROSS DATE 11/09/03	THIRD ANGLE PROJECTION REVISE ON CAD ONLY TITLE WIRE NUT CONNECTORS SCREW-ON TYPE MATERIAL NO. SEE CHART DOCUMENT NO. SD-19160-005 SHEET NO. 1 OF 1	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	B