

## VG H M25 MS

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

### Similar to illustration



In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

### General ordering data

Version	VG H (HDC halved cable gland), Cable glands, straight, M 25, 8 mm, OD min. 8.5 - OD max. 18 mm, IP65, Brass, nickel-plated
Order No.	<a href="#">1921740000</a>
Type	VG H M25 MS
GTIN (EAN)	4032248563012
Qty.	25 pc(s).

Creation date January 27, 2023 12:55:31 PM CET

Catalogue status 24.01.2023 / We reserve the right to make technical changes.

## VG H M25 MS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Width	25 mm	Width (inches)	0.984 inch
Net weight	18.76 g		

## Temperatures

Operating temperature	-20 °C...60 °C	Operating temperature, min.	-20 °C
Operating temperature, max.	60 °C		

## General information

AF size	25 mm	AF size 1	25 mm
Cable glands	metric, M 25	External thread	M 25
Halogen	Yes	Length of thread	8 mm
Material	Brass, nickel-plated	Notch multi-layer sealing diameter 1	8.5 mm
Notch multi-layer sealing diameter 2	11.5 mm	Notch multi-layer sealing diameter 3	14.5 mm
Notch multi-layer sealing diameter 4	18 mm	O-Ring	NBR
Operating temperature range, max.	60 °C	Operating temperature range, min.	-20 °C
Outer cable diameter, max.	18 mm	Outer cable diameter, min.	8.5 mm
Pitch of thread	1.5 mm	Protection degree	IP65
Protection degree with GWDR	IP65	Sealing	NBR

## Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ETIM 8.0	EC000441	ECLASS 9.0	27-14-44-32
ECLASS 9.1	27-14-44-32	ECLASS 10.0	27-14-44-32
ECLASS 11.0	27-14-44-32	ECLASS 12.0	27-14-08-01

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
SCIP	b5ff1f66-ddba-4739-9fc0-0521ddb52139

## Approvals

Approvals



ROHS Conform

## Downloads

Engineering Data	<a href="#">WSCAD</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	