

1934335-1 ✓ ACTIVE

## Z-PACK

TE Internal #: 1934335-1

High Speed Backplane Connectors, Board-to-Board, 54 Position,  
Mating Alignment, Guide Slot Mating Alignment Type, 9 Row, 6  
Column, PCB Mount Header

[View on TE.com >](#)



Connectors > PCB Connectors > Backplane Connectors > High Speed Backplane Connectors



Connector System: **Board-to-Board**

Number of Positions: **54**

Row-to-Row Spacing: **1.4 mm [ .055 in ]**

Mating Alignment: **With**

Mating Alignment Type: **Guide Slot**

## Features

### Product Type Features

Backplane Module Type	Center
Signal Arrangement	Differential
Connector System	Board-to-Board
PCB Connector Assembly Type	PCB Mount Header
Shroud Style	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

### Configuration Features

Pairs per Column	3
Number of Pairs	18
Stackable	No
Number of Signal Positions	36
Number of Positions	54
Number of Rows	9
Number of Columns	6
Backplane Architecture	Traditional Backplane
PCB Mount Orientation	Vertical
Guide Location	Center



### Electrical Characteristics

UL Voltage Rating	250 VAC
Impedance	100 $\Omega$
Operating Voltage	250 VAC

### Signal Characteristics

Differential Impedance	100 $\Omega$
Number of Differential Pairs per Column	3
Data Rate	10 Gb/s

### Contact Features

Contact Mating Area Length	6 mm [.236 in]
PCB Contact Termination Area Plating Material Thickness	.5 $\mu\text{m}$ [20 $\mu\text{in}$ ]
Contact Type	Pin
Contact Mating Area Plating Material Thickness	.76 $\mu\text{m}$ [29.92 $\mu\text{in}$ ]
Contact Mating Area Plating Material	Gold
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Rectangular
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	.5 A

### Termination Features

Termination Post & Tail Length	2.5 mm [.098 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit

### Mechanical Attachment

Guide Hardware	Without
Mating Retention	Without
PCB Mount Alignment	Without
PCB Mount Retention	With
PCB Mount Retention Type	Action/Compliant Tail
Mating Alignment	With
Mating Alignment Type	Guide Slot
Connector Mounting Type	Board Mount

### Housing Features

--	--



Number of Shrouded Sides	2
End Wall Location	Open
Housing Material	LCP (Liquid Crystal Polymer)
Housing Color	Black
Centerline (Pitch)	1.9 mm[.075 in]

### Dimensions

Connector Length	11.55 mm
Connector Height	11.8 mm
Connector Width	16 mm
PCB Hole Diameter	.47 mm
Row-to-Row Spacing	1.4 mm[.055 in]

### Usage Conditions

Operating Temperature Range	-65 – 90 °C[-85 – 194 °F]
-----------------------------	---------------------------

### Operation/Application

Circuit Application	Signal
---------------------	--------

### Industry Standards

UL Rating	Recognized
UL File Number	E28476
Agency/Standard	UL
UL Flammability Rating	UL 94V-0

### Packaging Features

Packaging Method	Tube
------------------	------

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per



homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



TE Part # 1934227-1  
Tin man Recpt Assy 3 Pair 6 Column



TE Part # 1976930-1  
INS TOOL, TIN MAN, 4.5



TE Part # 1976935-1  
EXT TOOL. IND CONTACTS, T.M.

### Customers Also Bought



TE Part #1-1734260-4  
1.25 WTB HDR SMT, 14 POS



TE Part #1-2007562-7  
SFP+assy 2x6 EMI Spg Outer LP Sn Enhance



TE Part #10104043-20  
SMT Photo Optic Emitter 663/890



TE Part #Y5015-000000077955  
GROMMET



TE Part #1658015-1  
MSB0.80PL11ASY040FL,-,10,-TY



TE Part #1-2132415-9  
EP2.5 Shrouded HDR ASSY 19P VERT w/oboss



TE Part #1934227-1  
Tin man Recpt Assy 3 Pair 6 Column



TE Part #1969605-2  
2P PM PLUG VAL-U-LOK PM GW



TE Part #6368062-1  
2X4 OFFSET STK MJ,SHLD,W/LED

## Documents

### Product Drawings

[TinMan Header Assy 3x6 open](#)

English

### CAD Files

Customer View Model

[ENG\\_CVM\\_1934335-1\\_A.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_1934335-1\\_A.3d\\_stp.zip](#)

English

Customer View Model

[ENG\\_CVM\\_1934335-1\\_A.2d\\_dxf.zip](#)

English

### 3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Product Specifications

[Application Specification](#)

English