

# Printed-circuit board connector - MCDNV 1,5/ 3-G1-3,5 P14THR - 1952982

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PCB headers, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 3, pitch: 3.5 mm, color: black, contact surface: Tin, mounting: THR soldering, The pin length is 1.4 mm. User information and design recommendations on Through Hole Reflow Technology can be found at: Downloads".

The figure shows a 10-pos. version with 20 contacts

## Your advantages

- Designed for integration into the SMT soldering process
- Vertical connection enables multi-row arrangement on the PCB
- Maximum flexibility when it comes to device design – one header for connectors with different connection technologies
- Conductor connection on several levels enables higher contact density



## Key Commercial Data

|              |               |
|--------------|---------------|
| Packing unit | 50 pc         |
| GTIN         |               |
| GTIN         | 4017918920180 |

## Technical data

### Dimensions

|                          |              |
|--------------------------|--------------|
| Length [ l ]             | 15.2 mm      |
| Width                    | 12 mm        |
| Pitch                    | 3.5 mm       |
| Dimension a              | 7 mm         |
| Width [ w ]              | 12 mm        |
| Height [ h ]             | 14.7 mm      |
| Height                   | 13.3 mm      |
| Length of the solder pin | 1.4 mm       |
| Pin dimensions           | 0.8 x 0.8 mm |
| Pin spacing              | 3.50 mm      |

# Printed-circuit board connector - MCDNV 1,5/ 3-G1-3,5 P14THR - 1952982

## Technical data

### Dimensions

|        |         |
|--------|---------|
| Length | 15.2 mm |
|--------|---------|

### General

|  |                      |
|--|----------------------|
| Range of articles                      | MCDNV 1,5/...-G1-THR |
| Insulating material group              | IIIa                 |
| Rated surge voltage (III/3)            | 2.5 kV               |
| Rated surge voltage (III/2)            | 2.5 kV               |
| Rated surge voltage (II/2)             | 2.5 kV               |
| Rated voltage (III/3)                  | 160 V                |
| Rated voltage (III/2)                  | 160 V                |
| Rated voltage (II/2)                   | 250 V                |
| Connection in acc. with standard       | EN-VDE               |
| Nominal current $I_N$                  | 8 A                  |
| Maximum load current                   | 8 A (per position)   |
| Insulating material                    | LCP                  |
| Flammability rating according to UL 94 | V0                   |
| Color                                  | black                |
| Number of positions                    | 3                    |

### Standards and Regulations


|  |        |
|--|--------|
| Connection in acc. with standard       | EN-VDE |
|  | CUL    |
| Flammability rating according to UL 94 | V0     |

### Environmental Product Compliance


|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Drawings

Drilling diagram



Dimensional drawing



# Printed-circuit board connector - MCDNV 1,5/ 3-G1-3,5 P14THR - 1952982

## Approvals


### Approvals


#### Approvals


IECEE CB Scheme / VDE Gutachten mit Fertigungsüberwachung / EAC / cULus Recognized


#### Ex Approvals

### Approval details

|                    |   |   |                |
|--------------------|---|---|----------------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-60987-B1B2 |
| Nominal voltage UN |   | 160 V   |                |
| Nominal current IN |   | 8 A   |                |

|   |   |   |          |
|---|---|---|----------|
| VDE Gutachten mit Fertigungsüberwachung |  | <a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a> | 40011723 |
| Nominal voltage UN                      |   | 160 V   |          |
| Nominal current IN                      |   | 8 A   |          |

|     |   |         |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

|                    |   |   |                 |
|--------------------|---|---|-----------------|
| cULus Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-20110128 |
|                    |   | D   | B               |
| Nominal voltage UN |   | 150 V   | 150 V           |
| Nominal current IN |   | 8 A   | 8 A             |

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>