


MICRO COMBICON Headers for Through Hole Reflow Applications MC(V) 0,5/...G-2,5 THT 2.5 mm Pitch

The consistent use of Through Hole Reflow plug connectors has also made it necessary to extend the COMBICON THR range to include the miniature pitch of 2.5 mm. The new THR MICRO COMBICON headers are of high-temperature resistant plastic and are ideally suited for the SMT reflow processes commonly encountered in industrial environments.

The possibility of being able to process the THR header together with SMD components in just one step using the PIN IN PASTE process, extends the scope of performance of the compact and space-saving MICRO plug connector. The familiar standard component family is now available with 2-12 positions as both vertical and horizontal version, as THR component.

The MC(V) 0,5-THT pin strips are equipped with 3.5 mm standard solder pins, and versions with short solder pins are also available on request. In combination with the through contacted drilled holes, the THR pin strips achieve the same high degree of mechanical stability as the headers soldered using the wave soldering process. The articles are available in loosely packaged form, but can also be supplied on request in a 44 mm wide tape.



COMBICON Select

The COMBICON search engine with CAD downloading




COMBICON Select – the printed circuit board connection software supports your workflow from the PCB and housing layout to the ordering process with:

- Systematic and fast selection of products
- Universal Internet aided engineering with extensive CAD downloading
- Easy-to-use e-shopping functions.

<http://select.phoenixcontact.com>



MC 0,5/...-G-2,5 THT 2.5 mm Pitch




Note:

COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
Headers, plug-in direction parallel to the conductor axis, 2.5 mm pitch, color: black,	2	2.5	MC 0,5/2-G-2,5 THT	19 63 42 1	50
	3	5	MC 0,5/3-G-2,5 THT	19 63 43 4	
	4	7.5	MC 0,5/4-G-2,5 THT	19 63 44 7	
	5	10	MC 0,5/5-G-2,5 THT	19 63 45 0	
	6	12.5	MC 0,5/6-G-2,5 THT	19 63 46 3	
	7	15	MC 0,5/7-G-2,5 THT	19 63 47 6	
	8	17.5	MC 0,5/8-G-2,5 THT	19 39 30 3	
	9	20	MC 0,5/9-G-2,5 THT	19 63 49 2	
	10	22.5	MC 0,5/10-G-2,5 THT	19 63 50 2	
	11	25	MC 0,5/11-G-2,5 THT	19 63 51 5	
	12	27.5	MC 0,5/12-G-2,5 THT	19 39 31 6	
(1) Coding profile , is inserted into the groove on the header after reflow-soldering, made of red plastic			CP-MC 0,5	18 81 43 5	100
Technical data			see description		
Dimensions		[mm]	2.5		
Pitch		[mm]	*) ≤ 8-pos. = 1.2 / > 8-pos. = 1.3		
Hole diameter		[mm]	0.8 x 0.8		
Pin dimensions		[mm]			
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		—	IIIa		
Surge voltage category / contamination class		—/—	III / 3	III / 2	II / 2
Rated voltage		[V]	32	160	160
Rated surge voltage		[kV]	1.5	2.5	2.5
Nominal current / cross section		[A]/[mm²]	4 / —		
Maximum load current / cross section		[A]/[mm²]	4 / —		
Insulating material			PA		
Inflammability class in acc. with UL 94			V0		
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes	UL/CUL: [V]/[A]/AWG CSA: [V]/[A]/AWG		applied for —		





MCV 0,5/...-G-2,5 THT 2.5 mm Pitch



Note:

COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
Headers, plug-in direction vertical to the conductor axis, 2.5 mm pitch, color: black,	2	2.5	MCV 0,5/2-G-2,5 THT	19 63 53 1	50
	3	5	MCV 0,5/3-G-2,5 THT	19 63 54 4	
	4	7.5	MCV 0,5/4-G-2,5 THT	19 63 55 7	
	5	10	MCV 0,5/5-G-2,5 THT	19 63 56 0	
	6	12.5	MCV 0,5/6-G-2,5 THT	19 63 57 3	
	7	15	MCV 0,5/7-G-2,5 THT	19 63 58 6	
	8	17.5	MCV 0,5/8-G-2,5 THT	19 63 59 9	
	9	20	MCV 0,5/9-G-2,5 THT	19 63 60 9	
	10	22.5	MCV 0,5/10-G-2,5 THT	19 63 61 2	
	11	25	MCV 0,5/11-G-2,5 THT	19 63 62 5	
	12	27.5	MCV 0,5/12-G-2,5 THT	19 63 63 8	
	(1) Coding profile , is inserted into the groove on the header after reflow-soldering, made of red plastic			CP-MC 0,5	
Technical data			see description		
Dimensions			2.5		
Pitch		[mm]	*) ≤ 8-pos. = 1.2 / > 8-pos. = 1.3		
Hole diameter		[mm]	0.8 x 0.8		
Pin dimensions		[mm]			
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		—	III / 3	IIIa	II / 2
Surge voltage category / contamination class		—/—	32	160	160
Rated voltage		[V]	1.5	2.5	2.5
Rated surge voltage		[kV]		4 / —	
Nominal current / cross section		[A]/[mm²]		4 / —	
Maximum load current / cross section		[A]/[mm²]		PA	
Insulating material				V0	
Inflammability class in acc. with UL 94					
Approval data (UL/CUL and CSA)			applied for		
Nominal voltage / current / conductor sizes			—		
			UL/CUL: [V]/[A]/AWG		
			CSA: [V]/[A]/AWG		



MC 0,5/...-G-2,5 THT R44 2.5 mm Pitch





Note:



COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
Headers packed in tapes, plug-in direction horizontal to the conductor axis, 2.5 mm pitch, color: black,	2	2.5	MC 0,5/2-G-2,5 THT R44	19 63 64 1	330
	3	5	MC 0,5/3-G-2,5 THT R44	19 63 65 4	
	4	7.5	MC 0,5/4-G-2,5 THT R44	19 63 66 7	
	5	10	MC 0,5/5-G-2,5 THT R44	19 63 67 0	
	6	12.5	MC 0,5/6-G-2,5 THT R44	19 63 68 3	
	7	15	MC 0,5/7-G-2,5 THT R44	19 63 69 6	
	8	17.5	MC 0,5/8-G-2,5 THT R44	19 63 70 6	
	9	20	MC 0,5/9-G-2,5 THT R44	19 63 71 9	
	10	22.5	MC 0,5/10-G-2,5 THT R44	19 63 72 2	
	11	25	MC 0,5/11-G-2,5 THT R44	19 63 73 5	
	12	27.5	MC 0,5/12-G-2,5 THT R44	19 63 74 8	
	(1) Coding profile , is inserted into the groove on the header after reflow-soldering, made of red plastic			CP-MC 0,5	
Technical data					
Dimensions			see description		
Pitch		[mm]	2.5		
Hole diameter		[mm]	≤ 8-pos. = 1.2 / > 8-pos. = 1.3		
Pin dimensions		[mm]	0.8 x 0.8		
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		—	III / 3	IIIa	II / 2
Surge voltage category / contamination class		—/—	32	160	160
Rated voltage		[V]	1.5	2.5	2.5
Rated surge voltage		[kV]		4 / —	
Nominal current / cross section		[A]/[mm²]		4 / —	
Maximum load current / cross section		[A]/[mm²]		PA	
Insulating material				V0	
Inflammability class in acc. with UL 94					
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes		UL/CUL: [V]/[A]/AWG	applied for		
		CSA: [V]/[A]/AWG	—		

MC 0,5/...-G-2,5 THT R44,
Tape width 44 mm, even nos. of positions,
feeder direction



MC 0,5/...-G-2,5 THT R44,
Tape width 44 mm, odd nos. of positions,
feeder direction



MCV 0,5/...-G-2,5 THT R44 2.5 mm Pitch



Note:

COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
Headers packed in tapes, plug-in direction vertical to the conductor axis, 2.5 mm pitch, color: black,	2	2.5	MCV 0,5/2-G-2,5 THT R44	19 63 75 1	330
	3	5	MCV 0,5/3-G-2,5 THT R44	19 63 76 4	
	4	7.5	MCV 0,5/4-G-2,5 THT R44	19 63 77 7	
	5	10	MCV 0,5/5-G-2,5 THT R44	19 63 78 0	
	6	12.5	MCV 0,5/6-G-2,5 THT R44	19 63 79 3	
	7	15	MCV 0,5/7-G-2,5 THT R44	19 63 80 3	
	8	17.5	MCV 0,5/8-G-2,5 THT R44	19 63 81 6	
	9	20	MCV 0,5/9-G-2,5 THT R44	19 63 82 9	
	10	22.5	MCV 0,5/10-G-2,5 THT R44	19 63 84 5	
	11	25	MCV 0,5/11-G-2,5 THT R44	19 63 85 8	
	12	27.5	MCV 0,5/12-G-2,5 THT R44	19 63 86 1	
(1) Coding profile , is inserted into the groove on the header after reflow-soldering, made of red plastic			CP-MC 0,5	18 81 43 5	100
Technical data			see description		
Dimensions			2.5		
Pitch		[mm]	≤ 8-pos. = 1.2 / > 8-pos. = 1.3		
Hole diameter		[mm]	0.8 x 0.8		
Pin dimensions		[mm]			
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		—	III / 3	IIIa	II / 2
Surge voltage category / contamination class		—/—	32	160	160
Rated voltage		[V]	1.5	2.5	2.5
Rated surge voltage		[kV]		4 / —	
Nominal current / cross section		[A]/[mm²]		4 / —	
Maximum load current / cross section		[A]/[mm²]		PA	
Insulating material				V0	
Inflammability class in acc. with UL 94					
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes		UL/CUL: [V]/[A]/AWG CSA: [V]/[A]/AWG	applied for —		

MCV 0,5/...-G-2,5 THT R44,
Tape width 44 mm, even and odd nos. of positions,
feeder direction

