

DB2.5/5.ADO



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products → Low Voltage Products and Systems → Connection Devices → Terminal Blocks → Solution Series

General Information

Extended Product Type:	DB2.5/5.ADO
Product ID:	1SNA399519R0000
EAN:	3472593995198
Catalog Description:	DB2.5/5.ADO IDC Terminal Blocks - Miniblocks ADO - screw clamp - Grey
Long Description:	- The mini blocks are particularly designed for applications where space is very restricted, - With the ABB ADO System®, experience the fastest and most reliable connection on the market, - This solution brings all the benefits of the ADO System® and allows installators to connect on standard screw clamp, - Easy base mounting thanks to the usage of flanges, - Up to 2 wires per connection in the ADO System® connection.

Ordering

Color:	Grey
Minimum Order Quantity:	100 piece
Customs Tariff Number:	85369010

Popular Downloads

Data Sheet, Technical Information:	1SNC160020C0201
Instructions and Manuals:	1SNC160020C0201

Dimensions

Product Net Width:	5 mm
Product Net Height:	31 mm
Product Net Depth / Length:	28 mm
Product Net Weight:	4 g

Technical

Rated Cross-Section:	1 mm ²
Spacing:	5 mm
Connection Type:	Screw clamp - ADO System
Function:	Miniblock
Number of Levels:	1
Connecting Capacity Main Circuit:	Screw Clamp / Flexible 1x 0.22 ... 2.5 mm ² Screw Clamp / Rigid 1x 0.2 ... 4 mm ²
Gauge Type:	A3
Rated Current (I_n):	Main Circuit 13.5 A

Rated Short-time Withstand Current (I_{cw}):	for 1 s 120 A
Rated Voltage (U_r):	800 V
Rated Impulse Withstand Voltage (U_{imp}):	8000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	3.5 mm
Tightening Torque:	acc. IEC 60947-1 0.4 N·m Manufacturer 0.6 N·m

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 24 ... 12 AWG Screw Clamp / Rigid 1x 24 ... 12 AWG
Connecting Capacity UL/CSA:	Stranded 18 AWG
Flammability According to UL94:	V0

Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225025U1000
EAC Certificate:	1SND161009A1100
Environmental Information:	1SND220024E1003
Instructions and Manuals:	1SNC160020C0201
RoHS Information:	1SND230472F0201

Classifications

Object Classification Code:	X
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
ETIM 6:	EC000897 - Feed-through terminal block

Container Information

Package Level 1 Units:	100 piece
-------------------------------	-----------

Package Level 1 Width:	135 mm
Package Level 1 Depth / Length:	175 mm
Package Level 1 Height:	74 mm
Package Level 1 Gross Weight:	0.4 kg
Package Level 1 EAN:	3472593995198
Package Level 2 Units:	1600 piece
Package Level 2 Width:	300 mm
Package Level 2 Depth / Length:	500 mm
Package Level 2 Height:	300 mm
Package Level 2 Gross Weight:	6.9 kg
Package Level 3 Units:	38400 piece
Product Packing Type:	Box

