

2042162-1 ✓ ACTIVE

Z-PACK | Z-PACK Slim UHD


TE Internal #: 2042162-1

High Speed Backplane Connectors, Board-to-Board, 96 Position,
Mating Alignment, Polarization Mating Alignment Type, 8 Row, 12
Column, Z-PACK Slim UHD

[View on TE.com >](#)



Connectors > PCB Connectors > Backplane Connectors > High Speed Backplane Connectors



Connector System: **Board-to-Board**

Number of Positions: **96**

Row-to-Row Spacing: **1.25 mm [.05 in]**

Mating Alignment: **With**

Mating Alignment Type: **Polarization**

Features

Product Type Features

Backplane Module Type	Center
Connector System	Board-to-Board
PCB Connector Assembly Type	PCB Mount Header
Shroud Style	Unshrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Pairs per Column	8
Number of Pairs	48
Stackable	Yes
Number of Signal Positions	96
Number of Positions	96
Number of Rows	8
Number of Columns	12



PCB Mount Orientation	Right Angle
-----------------------	-------------

Electrical Characteristics

Impedance	30 Ω
Operating Voltage	30 VAC

Signal Characteristics

Data Rate	20 Gb/s
-----------	---------

Body Features

Shield Material	Copper Alloy
-----------------	--------------

Contact Features

PCB Contact Termination Area Plating Material Thickness	.5 – 2.5 μm[20 – 100 μin]
Contact Type	Pin
Contact Shape & Form	Dual Beam
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	.5 A

Termination Features

Termination Post & Tail Length	1.6 mm[.493 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit

Mechanical Attachment

Mating Retention	Without
PCB Mount Alignment	With
Guide Hardware	Without
PCB Mount Retention	With
PCB Mount Retention Type	Action/Compliant Tail
Mating Alignment	With
Mating Alignment Type	Polarization

Housing Features

Number of Shrouded Sides	0
End Wall Location	None
Housing Material	LCP (Liquid Crystal Polymer)
Housing Color	Natural



Centerline (Pitch)	1.45 mm[.057 in]
--------------------	------------------

Dimensions

Connector Length	17.3 mm[.681 in]
------------------	------------------

Stack Height	1.6 mm
--------------	--------

Connector Height	9.5 mm[.374 in]
------------------	-----------------

Connector Width	12.51 mm[.493 in]
-----------------	-------------------

PCB Thickness (Recommended)	1.2 mm
-----------------------------	--------

PCB Hole Diameter	.4 mm[.016 in]
-------------------	----------------

Row-to-Row Spacing	1.25 mm[.05 in]
--------------------	-----------------

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Durability Rating	200 Cycles
-------------------	------------

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Method	Tray
------------------	------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
-----------------------------------------------	-----------------------------------------

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
----------------------------------------	---------------------------------------------------------------------------------------------------------------------------------

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
-----------------	-------------------------------------------------------------------------------------

Solder Process Capability	Not applicable for solder process capability
---------------------------	----------------------------------------------

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1857657-1
Female Connector




TE Part # 1982738-1
Female Connector Telcordia

Also in the Series | Z-PACK Slim UHD



Hard Metric Backplane Connectors(2)



High Speed Backplane Connectors(14)

Customers Also Bought



TE Part #788862-2
PT30 XFP CONNECTOR



TE Part #5-100526-4
CODING DEV INSRT COLOR GREEN



TE Part #5406552-1
INV MJ,1X4,PNL GRD, LED (G/Y)



TE Part #6469002-1
HM-ZD 4PR HDR 80P 5.2MM



TE Part #2007198-2
SFP+ 1x1 Cage Assembly, Press-Fit



TE Part #5223955-2
TE UPM Ver Receptacle 3P STD Power



TE Part #1982738-1
Female Connector Telcordia



TE Part #2057592-2
CFP Guide Rail



TE Part #1551012-1
Vert.Male, Telcordia L3



TE Part #1551099-1
Vert.Male, Telcordia Pre-post 1x

Documents

Product Drawings

Right Angle Male Connector

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_2042162-1_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2042162-1_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2042162-1_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

UL Report



English