

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [2045230801](#)
Status: **Active**
Overview:
Description: 1.25mm Pitch, Micro-Lock Plus Receptacle Crimp Housing, Low-Halogen, Dual Row, Positive Lock, 8 Circuits, Black

Agency Certification

UL E29179

General

Product Family Crimp Housings
 Series [204523](#)
 Application Signal, Wire-to-Board
 Overview microlock_plus_wiretoboard_connector_system
 Product Name Micro-Lock Plus
 UPC 193264084166

Physical

Circuits (maximum) 8
 Color - Resin Black
 Flammability 94V-0
 Gender Receptacle
 Glow-Wire Capable No
 Keying to Mating Part None
 Lock to Mating Part Yes
 Material - Resin PBT
 Net Weight 0.211/mg
 Number of Rows 2
 Packaging Type Bag
 Panel Mount No
 Pitch - Mating Interface 1.25mm
 Pitch - Termination Interface 1.25mm
 Polarized to Mating Part Yes
 Temperature Range - Operating -40° to +105°C

Material Info

Reference - Drawing Numbers

Application Specification AS-505432-001-001
 Packaging Specification 2045239200SPK-200
 Product Specification 2045230001-PS-000, 2045231001-PS-000
 Sales Drawing 2045230002-SD-000

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
 D(2020)4578-DC (25
 June 2020)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[204523](#) Series

Mates With

Micro-Lock Plus PCB Header [207760](#)