

Data sheet | Item number: 2050-1291

End and intermediate plate; 1.1 mm thick; gray

www.wago.com/2050-1291



Data

Physical data

Width	1.1 mm / 0.043 inch
Height	32.5 mm / 1.28 inch
Depth	25.2 mm / 0.992 inch

Material data

Color	gray
Flammability class per UL94	V0
Fire load	0.028 MJ
Weight	0.9 g

Commercial data

PU (SPU)	100 (25) Stück
Packaging type	box

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Country of origin	DE
GTIN	4055143951357
Customs tariff number	85389099990

Downloads

Documentation

Additional Information

Technical explanations	03.04.2019	pdf 2.2 MB	Download
------------------------	------------	---------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 2050-1291	URL	Download
------------------------	-----	----------

CAE data

ZUKEN Portal 2050-1291	URL	Download
------------------------	-----	----------

EPLAN Data Portal 2050-1291	URL	Download
-----------------------------	-----	----------

	URL	Download
--	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2050-1291 End and intermediate plate; 1.1 mm thick; gray	URL	Download
--	-----	----------

Installation Notes

Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.