

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [2072630236](#)

Status: **Active**

Overview:

Description: 0.60mm Pitch Sliver Edge Card Connector, Straddle-Mount, 32 Gbps, 2.36mm PCB Thickness, 4C, 140 Circuits, with Metal Key

General

Product Family	Edge Card Connectors
Series	207263
Component Type	Edgecard to PCB
Data Rate	32.0 Gbps
Edge Card Thickness	1.57mm
High Power Bay (30.0A or more)	No
Orientation	Straddle-Mount
Overview	sliver_edgecard_connector_and_cable_assemblies
Product Name	Sliver
Standard Based	General
UPC	191130504251

Physical

(p)ower-(s)ignal Configuration	140s - 0p
Circuit Size Range	201-294 Circuits
Circuits (Loaded)	140
Color - Resin	Black
Durability (mating cycles max)	200
Keying to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Matte Tin
Material - Resin	Liquid Crystal Polymer
Net Weight	4.570/g
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	2.36mm
Packaging Type	Tray
Pitch - Mating Interface	0.60mm
Plating min - Mating	0.762µm
Plating min - Termination	2.540µm
Temperature Range - Operating	-55° to +85°C
Termination Interface: Style	Surface Mount

Electrical

Current - Maximum per Contact	1.1A
Voltage - Maximum	29V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Packaging Specification	2072630236-PS-000
Sales Drawing	2072630002-000

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2020)4578-DC (25
June 2020)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[207263](#) Series