

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [2118880004](#)  
**Status:** **Active**  
**Overview:** Coeur CST High-Current Interconnect System  
**Description:** Coeur CST High-Current 6.00mm Terminal Retention Housing for 4 AWG Cable

**Documents:**

|                                                                   |                                                                 |
|-------------------------------------------------------------------|-----------------------------------------------------------------|
| <a href="#">Drawing (PDF)</a>                                     | <a href="#">Packaging Specification 2118880000-PK-000 (PDF)</a> |
| <a href="#">Product Specification 2119410000-PS-000 (PDF)</a>     | <a href="#">Test Summary 2119410000-TS-000 (PDF)</a>            |
| <a href="#">Application Specification 2119410000-AS-000 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>            |

**General**

|                |                                                            |
|----------------|------------------------------------------------------------|
| Product Family | Accessories                                                |
| Series         | <a href="#">211888</a>                                     |
| Component Type | Terminal Position Assurance                                |
| Overview       | <a href="#">Coeur CST High-Current Interconnect System</a> |
| Product Name   | Coeur CST                                                  |
| UPC            | 193264103959                                               |

**Physical**

|                               |                |
|-------------------------------|----------------|
| Circuits (Loaded)             | 1              |
| Circuits (maximum)            | 1              |
| Color - Resin                 | Black          |
| Material - Resin              | Polyester      |
| Net Weight                    | 2.734/g        |
| Packaging Type                | Bag            |
| Temperature Range - Operating | -40° to +105°C |

**Material Info**

**Reference - Drawing Numbers**

|                           |                   |
|---------------------------|-------------------|
| Application Specification | 2119410000-AS-000 |
| Packaging Specification   | 2118880000-PK-000 |
| Product Specification     | 2119410000-PS-000 |
| Sales Drawing             | 2118880000-SD-000 |
| Test Summary              | 2119410000-TS-000 |



**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2020)4578-DC (25  
June 2020)

**Halogen-Free**

**Status**

**Not Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[211888 Series](#)

**Use With**

6.00mm Receptacle Housing [211942](#)