

213729-1 Product Details

Have a Question?

Chat with a Product Information Specialist



213729-1

TE Internal Number: 213729-1

Active

View 3D PDF

CPC (Circular Plastic) and Circular Metal-Shell Connectors

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

Product Highlights:

- Preloaded
- 14 Positions
- 14 Signal Positions
- 0 Power Positions
- Connector Style = Receptacle

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Add to My Part List Request Sample Find Similar Products Buy Product

Documentation & Additional Information

Product Drawings:

- [RECEPTACLE ASSEMBLY, POSTED, SERIES 1, REVERSE SEX, CPC](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- [Circular Plastic Connectors \(CPC\)](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version F1)
- [3D Model](#) (IGES, Version F1)
- [3D Model](#) (STEP, Version F1)

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Contact Arrangement](#)
- [Keying Options](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Mount](#) = Panel
- [Mount Angle](#) = Straight
- [Shell Size](#) = 17
- [PCB Mount Retention](#) = Without
- [Shell Type](#) = All Plastic
- [Product Series](#) = Series 1
- [Thread Size](#) = 15/16-20 UNEF-2A
- [Sealed](#) = No
- [Mating Polarization Type](#) = Keyed
- [Comment](#) = Posts are 0.43 [.017] offset from centerline of contacts. All posts must be oriented in the same plane for proper contact/post location.

Mechanical Attachment:

- [Number of Power Positions](#) = 0
- [Mating Retention Type](#) = Threaded Coupling
- [VDE Tested](#) = No
- [Keying](#) = A

Termination Related Features:

- [Termination Method](#) = Solder
- [Termination End Plating](#) = Tin-Lead over Copper
- [Termination Post Length \(mm \[in\]\)](#) = 9.35 [0.368]

Body Related Features:

- [Number of Positions](#) = 14
- [Number of Signal Positions](#) = 14
- [Mount Style](#) = Flange with Mounting Holes
- [Fluid Resistance](#) = None

Contact Related Features:

- [Preloaded](#) = Yes
- [Contact Type](#) = Socket
- [Contact Termination Type](#) = Through Hole
- [Contact Plating, Mating Area, Material](#) = Gold (30)
- [Standard or Reverse Gender](#) = Reverse
- [Contact Base Material](#) = Brass

Housing Related Features:

- [Connector Style](#) = Receptacle
- [Housing Material](#) = Thermoplastic - GF
- [Housing Color](#) = Black
- [UL Flammability Rating](#) = UL 94V-0

Configuration Related Features:

- [Environmental Protection](#) = Without
- [Reverse Numbering](#) = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Conditions for Usage:

- [Applies To](#) = Printed Circuit Board

Other:

- [Brand](#) = AMP

BOOKMARK

Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)

Sign up for our eNewsletter

Enter your email address

Follow Us On:



Visit Us On:

