

- Unique floating contacts compensate for the effects of unevenly screened solder paste.
- Available packaged in tubes or on tape & reel per EIA-481.
- High temp. Nylon 46 insulator, is suitable for infra-red & vapor phase soldering. Closed frame insulator is vision system compatible.
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 218 for details.
- Series 214 use MM #1434 pins. See page 133 for details.

Total number of pins				Ordering Information				
	A	B	C	QTY PER TUBE	TUBE PACKAGING	TAPE & REEL PACKAGING	TAPE WIDTH (mm)	QTY PER REEL
VACUUM PAD TOP SURFACE ONLY								
6	7,6	7,62	10,1	67	214-XX-306-01-670800	214-XX-306-01-670799	16	750
8	10,1	7,62	10,1	50	214-XX-308-01-670800	214-XX-308-01-670799	16	1000
14	17,7	7,62	10,1	28	214-XX-314-01-670800	214-XX-314-01-670799	32	750
16	20,3	7,62	10,1	25	214-XX-316-01-670800	214-XX-316-01-670799	32	750
18	22,8	7,62	10,1	22	214-XX-318-01-670800	214-XX-318-01-670799	44	750
20	25,3	7,62	10,1	20	214-XX-320-01-670800	214-XX-320-01-670799	44	750
VACUUM PAD TOP AND BOTTOM								
24	30,4	15,24	17,7	16	214-XX-624-01-670800	214-XX-624-01-670799	44	400
28	35,5	15,24	17,7	14	214-XX-628-01-670800	214-XX-628-01-670799	56	400
32	40,6	15,24	17,7	12	214-XX-632-01-670800	214-XX-632-01-670799	56	400
40	50,8	15,24	17,7	10	214-XX-640-01-670800	NOT AVAILABLE		

For Electrical, Mechanical & Environmental Data, See pg. 4

XX=Plating Code See Below

For RoHS compliance select ◇ plating code.

RoHS 2002/95/EC

SPECIFY PLATING CODE XX=				99			44 ◇
Sleeve (Pin)				5,08µm Sn/Pb			5,08µm Sn
Contact (Clip)				5,08µm Sn/Pb			5,08µm Sn