

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	27APR2017	DW	CW
	A1	ECR-25-246355	12JUN2025	SC	RB

WIRE RANGE

M32X 1.5

(33)

8

40

(Ø 44)

NOTES / 注解:

1. TECHNICAL CHARACTERISTICS / 技术参数:

SHELL MATERIAL / 主体材料: NICKEL PLATED BRASS / 铜镀镍

SEAL MATERIAL / 密封材料: RUBBER, BLACK

PINCH RING MATERIAL / 夹紧件材料: NYLON, GREY

OPERATION TEMPERATURE / 工作温度: $-40^{\circ}\text{C} - +100^{\circ}\text{C}$

PROTECTION DEGREE / 防护等级: IP68

WIRE RANGE / 夹线范围: 18-25 mm

T3707320103-000

DLX-32-MC (18~25)
电磁屏蔽金属接头 M32 (18-25)PART NUMBER
料号PART DESCRIPTION
描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 27APR2017
DAVID WANG

CHK 27APR2017
CHRIS WANG

APVD 27APR2017
XIANG XU

NAME
DLX-32-MC (18-25)

DIMENSIONS:
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

MATERIAL

FINISH

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	©-T3707320103000	-

CUSTOMER DRAWING

SCALE 1:1 SHEET 1 OF 1 REV A1

1470-19 (3/13)