

# Front adapters - FLK 50-PA/EZ-DR/KS/2000/YOC



2314561

<https://www.phoenixcontact.com/de/produkte/2314561>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Cast front adapter with attached round cable and a 50-pos. socket strip injection-molded on both sides for the connection of Yokogawa ProSafe controllers. Cable length: 20.0 m

## Commercial Data

Item number	2314561
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	I1 - Systemverkabelung
Product Key	CK2154
Catalog Page	Page 190 (IF-2007)
GTIN	4046356133708
Weight per Piece (including packing)	4.256 g
Weight per Piece (excluding packing)	4.062 g
Customs tariff number	85444290
Country of origin	DE

## Technical Data

### Notes

Notes on operation	No additional touch protection is required when using a SELV/PELV voltage ( $\leq 25$ V AC or 60 V DC).
--------------------	---

### Product properties

Product type	Front adapter
--------------	---------------

#### Insulation characteristics

Overvoltage category	II
Pollution degree	2
Insulation	Functional insulation

### Electrical properties

Max. permissible operating voltage	30 V DC
Max. permissible current	500 mA (per path)
Nominal operating mode	100% operating factor
Rated insulation voltage	63 V
Rated surge voltage	0.6 kV

#### Supported controller YOKOGAWA ProSafe-RS

Suitable I/O card	SDV531
-------------------	--------

### Connection data

#### Controller level

Connection method	Yokogawa, I/O cards compatible
Number of connections	1
Number of positions	50

#### Field level

Connection method	Yokogawa, KS compatible
Number of connections	1
Number of positions	50

### Dimensions

Length	20 m
--------	------

### Cable / line

Cable length	20 m
--------------	------

#### 50X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	50
Shielded	yes

2314561

<https://www.phoenixcontact.com/de/produkte/2314561>

Cable type	50X0.14 [PVC]
Conductor type	Assembled shielded round cable
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	50x 0.14 mm <sup>2</sup>
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	11 mm ±0.3 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (at 20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	114 mm
Smallest bending radius, movable installation	205 mm
Max. bending cycles	5000 (at a radius of ≥ 18x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Degree of protection Installation location	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation)
	-10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

## Approval data

### UKCA

Certificate	UKCA-compliant
-------------	----------------

## Standards and regulations

### Air clearances and creepage distances

Standards/regulations	DIN EN 50178
-----------------------	--------------

## Mounting

Mounting position	any
-------------------	-----

2314561

<https://www.phoenixcontact.com/de/produkte/2314561>

## Drawings

Connection diagram

50-pos. connector to the I/O card	50-pos. connector to the module	Wire color
1	50	black
2	49	brown
3	48	red
4	47	orange
5	46	yellow
6	45	green
7	44	blue
8	43	violet
9	42	gray
10	41	white
11	40	white-black
12	39	white-brown
13	38	white-red
14	37	white-orange
15	36	white-yellow
16	35	white-green
17	34	white-blue
18	33	white-violet
19	32	white-gray
20	31	brown-black
21	30	brown-red
22	29	brown-orange
23	28	brown-yellow
24	27	brown-green
25	26	brown-blue
26	25	brown-violet
27	24	brown-gray
28	23	brown-white
29	22	green-black
30	21	green-brown
31	20	green-red
32	19	green-orange
33	18	green-blue
34	17	green-violet
35	16	green-gray
36	15	green-white
37	14	yellow-black
38	13	yellow-brown
39	12	yellow-red
40	11	yellow-orange
41	10	yellow-blue
42	9	yellow-violet
43	8	yellow-gray
44	7	yellow-white
45	6	gray-black
46	5	gray-brown
47	4	gray-red
48	3	gray-orange
49	2	gray-yellow
50	1	gray-green

# Front adapters - FLK 50-PA/EZ-DR/KS/2000/YOC



2314561

<https://www.phoenixcontact.com/de/produkte/2314561>

## Approvals



### EAC

Approval ID: RU\*-DE.HB\*35.B00385



### UL Listed

Approval ID: FILE E 238705

	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	125 V	0.5 A	-	-



### cUL Listed

Approval ID: FILE E 238705

	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	125 V	0.5 A	-	-

### cULus Listed

2314561

<https://www.phoenixcontact.com/de/produkte/2314561>

## Classifications

### ECLASS

ECLASS-9.0	27242292
ECLASS-10.0.1	27242292
ECLASS-11.0	27242292

### ETIM

ETIM 8.0	EC002584
----------	----------

### UNSPSC

UNSPSC 21.0	32151600
-------------	----------

# Front adapters - FLK 50-PA/EZ-DR/KS/2000/YOC



2314561

<https://www.phoenixcontact.com/de/produkte/2314561>

## Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

2314561

<https://www.phoenixcontact.com/de/produkte/2314561>

## Accessories

### Screw set

Screw set - VF-SCREW-YOKOGAWA/M3X18/DCS - 2902873

<https://www.phoenixcontact.com/de/produkte/2902873>



Replacement screw M3x18 for Yokogawa system cable, front adapter control side.

---

### Screw set

Screw set - VF-SCREW-YOKOGAWA/M4X25/KS - 2902874

<https://www.phoenixcontact.com/de/produkte/2902874>



Replacement screw M4x25 for Yokogawa system cable, module side.

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH

Flachmarktstraße 8

D-32825 Blomberg

+49 52 35/3-1 20 00

[info@phoenixcontact.de](mailto:info@phoenixcontact.de)