

Item no.: 235-771  
 Product description: 1-CONDUCTOR PCB TERMINAL BLOCK 2 SOLDER PINS /  
 POLE 1 POLE PIN SPACING 3.81 MM / 0.15 IN WITH PUSH  
 BOTTOMS



Produkt kann von Bild abweichen / product may differ

Packing unit 800 8\*100 pieces

RoHS compliant

Weight	0.547 g
Color	gray
No. of connection Points	1
No. of potentials	1
pole count	1
Height	15.5 mm
Height	0.61 in
Width	3.81 mm
Width	0.15 in
Depth	12.5 mm
Depth	0.492 in
Pin spacing from	3.81 mm
Pin spacing from	0.15 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	17.5 A
Pollution degree	2

Measured voltage EN	500 V
Measured shock voltage	4 kV
Current intensity EN	17.5 A
Cross section [mm <sup>2</sup> ]	0.5 - 1.5 mm <sup>2</sup>



Wiring method	solid
Cross section [mm <sup>2</sup> ]	0.75 - 1.5 mm <sup>2</sup>
Wiring method	fine-stranded
Cross section [mm <sup>2</sup> ]	0.25 - 1 mm <sup>2</sup>
Wiring method	fine-stranded (with ferrule and plastic collar)
Cross section [mm <sup>2</sup> ]	0.25 - 1 mm <sup>2</sup>
Wiring method	fine-stranded (with ferrule, without plastic collar)
Cross section [AWG]	20 - 16 AWG
Strip length from	9 mm
Strip length to	10 mm
Material group	I
Contact material	Electrolytic copper (Ecu)
Contact surface	tin-plated



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
235-771	CCA	NL6309	250	10	0,5-1,5
235-771	KEMA	2110204.16	250	10	0,5-1,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected