

KVM extender - VL KVM EXTENDER - 2404770

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Provides the ability to extend the keyboard, video, and mouse signals up to 90 m from the IPC



Product Description

The VL KVM EXTENDER... provides the ability to extend the keyboard, video, and mouse signals up to 90 m from the IPC. It supports full high-definition video and USB 2.0 signals, including keyboard, mouse, touch screen, and other functions.


The system is composed of a transmitter connected to an IPC and a receiver to which peripherals are connected. The transceiver and receiver are connected via a shielded CAT6 cable utilizing RJ45 connectors.

Your advantages

- ✓ LED indicators: USB, Video, Link, Power
- ✓ Flexible, thanks to remote operating solutions up to 90 m
- ✓ Increased system availability, thanks to the use of purely passive displays
- ✓ Cost-effective, thanks to elimination of cable and mounting costs
- ✓ Fast startup, thanks to a solution consisting purely of hardware



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 500089
GTIN	4055626500089
Weight per Piece (excluding packing)	2,300.000 g
Custom tariff number	85176200
Country of origin	Taiwan

Technical data

Note

KVM extender - VL KVM EXTENDER - 2404770

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

General

Note	The VL KVM Extender product has been tested and is compatible with all Phoenix Contact IPC and monitor products, with the exception of the VL IPC P7000 (2701127) product. Also, because there are a number of factors that may impact the operation of this product, there is no guarantee that non-Phoenix PC and monitor products will be compatible with the VL KVM Extender product
Scope of delivery	Includes VL KVM EXTENDER (TX), VL KVM EXTENDER (RX), one 1.8 m USB A to USB B cable, one 1.8 m DP++ cable, and one USB A to micro-B USB cable (for service connection)
Mounting type	DIN rail mounting
	Front installation
	Bookshelf mounting
Weight	1 kg

Computer data

Interfaces	1x USB 2.0, Typ B (VL KVM EXTENDER (TX))
	3x USB 2.0, Typ A (VL KVM EXTENDER (RX))
	1x micro-B USB
	1x RJ45
Monitor output	1x DisplayPort
	1x DVI-D

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-30 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (relative humidity, non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (relative humidity, non-condensing)
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Device supply

Power supply unit	24 V DC ±20 %
-------------------	---------------

Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
-------	--

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

KVM extender - VL KVM EXTENDER - 2404770

Classifications

eCl@ss

eCl@ss 10.0.1	19209290
eCl@ss 7.0	19209290
eCl@ss 8.0	19209290
eCl@ss 9.0	19209290

ETIM

ETIM 4.0	EC002584
ETIM 5.0	EC002584
ETIM 6.0	EC002584
ETIM 7.0	EC002584

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU* DE*08.B.00004/18
-----	--	-------------------------

Accessories

Accessories

Assembly adapter

Assembly adapters - UTA 107/30 - 2320089



Universal DIN rail adapter

KVM extender - VL KVM EXTENDER - 2404770

Accessories

Mounting material

Mounting kit - VL KVM EXTENDER BOOKSHELF MNT - 2404776



Bookshelf-style mounting kit for use with the VL KVM EXTENDER (2404770)

Connecting cable - VL 2.0M DP CABLE - 2404774



DisplayPort (DP) cable (2 m) for use with industrial computers
