

UV66-ADV-12-IPPC-1001.01**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The built-in IPPC 1000 is an entry-level industrial Panel PC. The robust and durable operating touch panels are available from 7" to 15.6" with resistive single- or capacitive multi-touch (BASIC or ADVANCED version).

Two Ethernet 10/100/1000Mbps ports with "Wake on Lan" support and multiple USB ports offer state-of-the-art-connectivity of the IPPC 1000. For data storage, the IPPC 1000 includes a 60GB SSD hard drive and a CFast card slot with external access. Equipped with the Intel Celeron™ J1900 2GHz 64 bit quad-core processor, 4GB RAM memory and the Windows 10 IoT Enterprise 2019 operating system, IPPC 1000 product family can be used in many ways.

General ordering data

Version	Industrial Panel-PC, Display size 12.1", Capacitive touch, MultiTouch, Front protection IP66
Order No.	2676480000
Type	UV66-ADV-12-IPPC-1001.01
GTIN (EAN)	4050118749571
Qty.	1 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2023-03-31

Creation date December 4, 2023 3:33:53 PM CET

Catalogue status 24.11.2023 / We reserve the right to make technical changes.

UV66-ADV-12-IPPC-1001.01

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	66 mm	Depth (inches)	2.598 inch
Height	234 mm	Height (inches)	9.213 inch
Width	331 mm	Width (inches)	13.031 inch
Wall thickness, min.	2 mm	Wall thickness, max.	6 mm
Net weight	2,600 g		

Temperatures

Storage temperature	-20 °C ... +60 °C	Operating temperature	0 °C ... +50 °C
Humidity	80 % relative humidity (without condensation)		

Equipment

Angle (horizontal)	Left: 88° / Right: 88°	Angle (vertical)	Top: 88° / Bottom: 88°
Luminance	400 cd/m ²	Material display	Glass
Material frame	Aluminium	Number of displayable colours	16 M
Resolution	1280 x 800	Size	12.1"
Touch-Screen	capacitive, MultiTouch		

General data

Current consumption	Voltage	24 V
	Current	1.42 A
Operating system	Windows 10 IoT Enterprise LTSC 2019 64bit	
Protection degree	IP66	
Voltage supply	24 V DC (18-32 V DC) isolated	

System data

Interfaces behind	2 x Ethernet 10/100/1000 MBit/s (RJ45), 1x USB 3.0, 1x USB 2.0, 1x Cfast slot	Memory	60 GB mSATA SSD
Memory (RAM)	4 GB, DDR3	Operating system	Windows 10 IoT Enterprise LTSC 2019 64bit
Processor	Intel® Celeron® J1900 - Quad Core 2.0 GHz (2.42 GHz Burst)		

Classifications

ETIM 6.0	EC001414	ETIM 7.0	EC001414
ETIM 8.0	EC001414	ETIM 9.0	EC001414
ECLASS 9.0	19-20-01-03	ECLASS 9.1	19-20-01-03
ECLASS 10.0	19-20-01-03	ECLASS 11.0	19-20-01-03
ECLASS 12.0	19-20-01-03	ECLASS 13.0	19200103

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
SCIP	c67eaff0-dbf6-4589-ba08-8f513fc6ba7f

UV66-ADV-12-IPPC-1001.01

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate no. (cULus)	E141197

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity - UV66-XXX-XX-IPPC-10XX.XX
Engineering Data	CAD data – STEP
User Documentation	QGUI UV66 IPPC10XX
Catalogues	Catalogues in PDF-format


UV66-ADV-12-IPPC-1001.01

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com


Drawings

Maße (mm) / Dimensions (mm)



	LCD	A	B	C	D	E
UV66-BAS-7-IPPC-1001.01	7"	215	167	39	18.6	4
UV66-BAS-10-IPPC-1001.01	10.1"	293	212	39	20	5
UV66-BAS-12-IPPC-1001.01	12.1"	331	234	39	32	5
UV66-BAS-15-IPPC-1001.01	15.6"	430	275	39	36	6
UV66-ADV-7-IPPC-1001.01	7"	204	148	39	18.6	4
UV66-ADV-10-IPPC-1001.01	10.1"	293	212	39	20	5
UV66-ADV-12-IPPC-1001.01	12.1"	331	234	39	22	5
UV66-ADV-15-IPPC-1001.01	15.6"	433	280.5	39	36	6

Montageausschnitt / Panel cut-out



	LCD	E (mm)	F (mm)
UV66-BAS-7-IPPC-1001.01	7"	207	159
UV66-BAS-10-IPPC-1001.01	10.1"	277	196
UV66-BAS-12-IPPC-1001.01	12.1"	313	216
UV66-BAS-15-IPPC-1001.01	15.6"	410	255
UV66-ADV-7-IPPC-1001.01	7"	197	141
UV66-ADV-10-IPPC-1001.01	10.1"	293	196
UV66-ADV-12-IPPC-1001.01	12.1"	313	128
UV66-ADV-15-IPPC-1001.01	15.6"	410	255

Montageabstände / Mounting distances



X	Y	Z
> 50 mm	> 100 mm	> 50 mm

Industrial panel PC (IPPC) 1000 series

