

PVN PCBA 1KV 6I6O SPD T2 F

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

**General ordering data**

Version	Photovoltaics, PCB, Combiner Box, 1000 V, 1 MPP, 6 Inputs / 6 Outputs per MPP, With fuse holder, Surge protection II
Order No.	2770550000
Type	PVN PCBA 1KV 6I6O SPD T2 F
GTIN (EAN)	4064675029632
Qty.	1 pc(s).

Creation date January 4, 2024 1:33:48 PM CET

Catalogue status 09.12.2023 / We reserve the right to make technical changes.

PVN PCBA 1KV 6I60 SPD T2 F

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	254 mm	Depth (inches)	10 inch
Height	69.2 mm	Height (inches)	2.724 inch
Width	440 mm	Width (inches)	17.323 inch
Net weight	915 g		

Approvals and norms

Approvals	EN 61439-2, IEC 61439-2
-----------	-------------------------

Electrical characteristics

Current per Maximum Power Point, max. 90 A

Rated DC current per connection	Rated current	15 A	
	Short-circuit at main output	Duration	10 h
		Factor	1.25 * I _{nc}
Rated short-term current resistance	Rated current	112.5 A	
Rated DC voltage	1,000 V		

Enclosure

Type of mounting	4 screws
------------------	----------

General data

Protection degree	IPO0	Standards	EN 61439-2:2011, IEC 61439-2 ed 2.0
-------------------	------	-----------	-------------------------------------

Inputs

Amount of maximum power points	1 MPPT		
Cartridge fuse	10 x 38 mm		
DC Input + & -	Wire connection	Type of connection	PUSH IN with actuator
		Compatible cable cross-section	TÜV 2 Pfg1169/08.07, EN 50618:2015
		Wire cross-section, min.	2.5 mm ²
		Wire cross-section, max.	50 mm ²
Fuse type	Empty fuse holder		
Fuse-link standard	gPV (EN 60269-6), IEC 60269-1, IEC 60269-6		
Max. number of DC inputs	per Maximum Power Point 6 inputs connected in parallel		
Surge protection auxiliary contact	Wire connection	Type of connection	Tension clamp connection with actuator
		Flexible, max. H05(07) V-K	1.5 mm ²
		w. wire end ferrule, DIN 46228 pt 1, max.	1.5 mm ²

PVN PCBA 1KV 6I60 SPD T2 F

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Outputs

DC Output + & -	Wire connection	Compatible cable crosssection	TÜV 2 Pfg 1169/08.07, EN 50618:2015
		Wire cross-section, min.	2.5 mm ²
		Wire cross-section, max.	16 mm ²

Max. number of DC outputs per Maximum Power Point 7 outputs connected in parallel

Surge protection DC side

Discharge current I_n (8/20 μ s)	20 kA	Discharge current, max. (8/20 μ s)	40 kA
PV system voltage, max. U_{cpv}	1,100 V	Protection level U_p (+/-)	≤ 3.8 kV
Protection level U_p (+/PE)	≤ 3.8 kV	Protection level U_p (-/PE)	≤ 3.8 kV
Requirements class	Type II	Short-circuit current I_{SCPV}	11,000 A
Standards	EN 61439-2:2011, IEC 61439-2 ed 2.0	Standby power consumption P_c	< 0.2 W
Total discharge current I_{total} (8/20 μ s)	50 kA		

Classifications

ETIM 6.0	EC002928	ETIM 7.0	EC002928
ETIM 8.0	EC003857	ETIM 9.0	EC003857
ECLASS 9.0	22-57-92-03	ECLASS 9.1	22-57-02-90
ECLASS 10.0	22-57-02-90	ECLASS 11.0	22-57-02-92
ECLASS 12.0	22-57-02-92	ECLASS 13.0	22570292

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Approvals

Approvals



ROHS Conform

Downloads

Technical Documentation	Drawing PVN PCBA 1KV 6I60 SPD T2 F
User Documentation	MANUAL PVN PCBA MULTI
Catalogues	Catalogues in PDF-format

PVN PCBA 1KV 6I6O SPD T2 F

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

