



+ CONNECTORS

## SEALS AND CAVITY PLUGS



TE CONNECTIVITY (TE)

### 070 TYPE NEW RUBBER PLUG S

2822356-1

TE Internal Number: 2822356-1

Always EU RoHS/ELV Compliant

Seal Type **Rubber Plug**

Cable Insulation Diameter **1.4 – 2.1 mm [ .055 – .083 in ]**

Material **NBR**

Resistance to Hydrocarbons **VARIABLE**

Shore A Hardness **40**

✓ Active

↓ **PRODUCT DRAWING**  
Japanese

↓ **3D PDF**

#### Product Drawings

#### [NEW RUBBER PLUG \(S\)](#)

PDF  
**Japanese**

#### CAD Files

#### [3D PDF](#)

PDF  
**3D**

#### [Customer View Model](#)

2D\_DXF.ZIP  
**English**

#### [Customer View Model](#)

3D\_IGS.ZIP  
**English**

#### [Customer View Model](#)

3D\_STP.ZIP  
**English**

#### Product Specifications

##### Product Specification

#### [AMP-ECONOSEAL "J"-II Connector](#)

PDF  
**Japanese**

#### [AMP-ECONOSEAL-J Mark II+ Connector](#)

PDF  
**English**

#### [AMP-ECONOSEAL-J Mark II+ Connector](#)

PDF  
**Japanese**

##### Qualification Test Report

#### [ECONOSEAL J MK-II+ CONNECTOR](#)

PDF  
**Japanese**



Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

|                       |           |                    |
|-----------------------|-----------|--------------------|
| Product Type Features | Seal Type | <b>Rubber Plug</b> |
|-----------------------|-----------|--------------------|

---

|               |          |              |
|---------------|----------|--------------|
| Body Features | Material | <b>NBR</b>   |
|               | Color    | <b>Black</b> |

---

|            |                           |  |
|------------|---------------------------|--|
| Dimensions | Cable Insulation Diameter | <b>1.4 – 2.1 mm [ .055 – .083 in ]</b> |
|------------|---------------------------|--|

---

|                  |                                  |   |
|------------------|----------------------------------|---|
| Usage Conditions | Operating Temperature (Max) (°C) | <b>65, 70, 75, 80, 85, 90, 100, 105</b>       |
|                  | Operating Temperature (Max) (°F) | <b>149, 158, 167, 176, 185, 194, 212, 221</b> |
|                  | Operating Temperature Range      | <b>-30 – 105 °C [ -22 – 221 °F ]</b>          |

---

|                    |                    |             |
|--------------------|--------------------|-------------|
| Packaging Features | Packaging Quantity | <b>1000</b> |
|                    | Packaging Method   | <b>Bag</b>  |

---

|       |                            |                 |
|-------|----------------------------|-----------------|
| Other | Resistance to Hydrocarbons | <b>VARIABLE</b> |
|       | Shore A Hardness           | <b>40</b>       |
|       | Lubricant Content          | <b>Yes</b>      |

---

|                    |  |
|--------------------|--|
| Product Compliance | <a href="#">Statement of Compliance</a><br>PDF |
|--------------------|--|

[VIEW ALL PRODUCT COMPLIANCE](#)