Interface module - UMK- EC56/32-XUL - 2975780

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Interface module; connection 1: Screw connection; connection 2: 1x ELCO connector (32-position) (Pin strip type 8016, left)

Key Commercial Data

Packing unit	1 pc
GTIN	4 017918 089108
GTIN	4017918089108

Technical data

Dimensions

Width	101.3 mm
Height	77 mm
Depth	58.5 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 40 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. perm. operating voltage	25 V AC
	60 V DC
Max. perm. current (per branch)	2 A
Max. permissible current (all branches)	32 A (32 branches with 1 A each)
Number of positions	32
Mounting position	any
Degree of protection	IP00

Connection data for connection 1

Connection name	Field level

Interface module - UMK- EC56/32-XUL - 2975780

Technical data

Connection data for connection 1

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	0.2 mm² ... 4 mm²
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 12

Connection data for connection 2

Connection name	Controller level
Connection method	ELCO connector
Number of connections	1
Number of positions	32
Note	Pin strip type 8016, left

Standards and Regulations


Standards/regulations	IEC 60664
	DIN EN 50178
Rated insulation voltage	85 V
Rated surge voltage	0.8 kV (Functional insulation)
Degree of pollution	2
Overvoltage category	II

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”

Drawings

Dimensional drawing



Approvals

Approvals

Interface module - UMK- EC56/32-XUL - 2975780

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC	EAC	RU C-DE.A*30.B.01742

Phoenix Contact 2019 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com