



For more Information
please call

1-800-Belden1



Description:

Belden's 1.00mm pitch gray ribbon cable was designed for the disk drive market where the 2.00mm IDC connector is widely used.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 26 | 28 | 7x36 | TC - Tinned Copper |

Conductor Spacing Center to Center: .0394 +/- .002

Conductor Spacing Outside Center to Outside Center: .984 +/- .008

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (in.) |
|--------------------------|----------------------|
| PVC - Polyvinyl Chloride | .010 |

Insulation Resistance: >10,000 Megaohms

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Overall Cable

Overall Nominal Thickness: .0354 +/- .0031

Overall Nominal Width: 1.02 +/- .008

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +105°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|-------------------------|
| UL AWM Style: | 2651 |
| UL Rating: | 105°C, 300 V RMS, VW-1 |
| CSA Specification: | AWM I A 105°C 300 V FT1 |
| CSA Rating: | 105°C, 300 V RMS, FT1 |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 07/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |

| | |
|-----------------------------------|-----|
| CA Prop 65 (CJ for Wire & Cable): | Yes |
|-----------------------------------|-----|

| | |
|-----------------------------|-----|
| MII Order #39 (China RoHS): | Yes |
|-----------------------------|-----|

Flame Test

| | |
|----------------|------|
| UL Flame Test: | VW-1 |
|----------------|------|

| | |
|-----------------|-----|
| CSA Flame Test: | FT1 |
|-----------------|-----|

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| Description | Impedance (Ohm) |
|-------------|-----------------|
| (GS) | 130 |
| (GSG) | 90 |

Nom. Inductance:

| Description | Inductance (μH/ft) |
|---------------|--------------------|
| @ 1 MHz (GS) | .24 |
| @ 1 MHz (GSG) | .16 |

Nom. Capacitance Conductor to Conductor:

| Description | Capacitance (pF/ft) |
|---------------|---------------------|
| @ 1 kHz (GSG) | 20 |
| @ 1 MHz (GS) | 9.5 |
| @ 1 MHz (GSG) | 16.5 |

Nominal Velocity of Propagation:

| Description | VP (%) |
|-------------|--------|
| | 69 |

Nominal Delay:

| Delay (ns/ft) |
|-------------------|
| 1.47 NS/FT. (GSG) |

Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 68.2 OHMS/1000 FT. MAX. |

Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 10 | 3.3 |
| 20 | 5.1 |
| 30 | 7 |
| 40 | 8.3 |
| 50 | 9.8 |
| 60 | 11.6 |
| 70 | 13.1 |
| 80 | 14.2 |
| 90 | 16.4 |
| 100 | 17.6 |

Max. Operating Voltage - Non-UL:

| Voltage |
|-----------|
| 300 V RMS |

Max. Recommended Current:

| Current |
|----------------------------|
| 1 Amp per conductor @ 20°C |

| | |
|-------------------------------|--------------|
| Dielectric Withstand Voltage: | 2, 000 V RMS |
|-------------------------------|--------------|

Typical Unbalanced Crosstalk:

| Description | Pulse Rise Time (NS) (MHz) | Near End % (MHz) | Far End % (MHz) |
|----------------------|----------------------------|------------------|-----------------|
| 10 ft. sample length | 3 | 4.3 | 6.7 |
| 10 ft. sample length | 5 | 3.8 | 3.4 |
| 10 ft. sample length | 7 | 3.6 | 2.5 |

Notes (Overall)

Notes: GSG=Ground-Signal-Ground Mode

Polarity Identification (Overall)

Polarity Identification: BLACK POLARITY STRIPE ON #1 CONDUCTOR

Related Documents:

No related documents are available for this product

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|-----------------|--------|-------------|-------|-------|-----------------------|
| 2L28026 008H100 | 100 FT | 3.100 LB | GRAY | | 26 #28 STR PVC RIBBON |

Revision Number: 1 Revision Date: 02-20-2009

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.