

# Small Signal MOSFET

60 V, 380 mA, Single, N-Channel, SOT-23

**2N7002K, 2V7002K**

## Features

- ESD Protected
- Low  $R_{DS(on)}$
- Surface Mount Package
- 2V Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

## Applications

- Low Side Load Switch
- Level Shift Circuits
- DC-DC Converter
- Portable Applications i.e. DSC, PDA, Cell Phone, etc.

## MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise stated)


| Rating                                                                    | Symbol         | Value                                                              | Unit             |
|---------------------------------------------------------------------------|----------------|--------------------------------------------------------------------|------------------|
| Drain-to-Source Voltage                                                   | $V_{DS}$       | 60                                                                 | V                |
| Gate-to-Source Voltage                                                    | $V_{GS}$       | $\pm 20$                                                           | V                |
| Drain Current (Note 1)<br>Steady State 1 sq in Pad                        | $I_D$          | $T_A = 25^\circ\text{C}$<br>380<br>$T_A = 85^\circ\text{C}$<br>270 | mA               |
| Drain Current (Note 2)<br>Steady State Minimum Pad                        | $I_D$          | $T_A = 25^\circ\text{C}$<br>320<br>$T_A = 85^\circ\text{C}$<br>230 | mA               |
| Power Dissipation<br>Steady State 1 sq in Pad<br>Steady State Minimum Pad | $P_D$          | 420<br>300                                                         | mW               |
| Pulsed Drain Current ( $t_p = 10 \mu\text{s}$ )                           | $I_{DM}$       | 5.0                                                                | A                |
| Operating Junction and Storage<br>Temperature Range                       | $T_J, T_{STG}$ | $-55$ to $+150$                                                    | $^\circ\text{C}$ |
| Source Current (Body Diode)                                               | $I_S$          | 300                                                                | mA               |
| Lead Temperature for Soldering Purposes<br>(1/8" from case for 10 s)      | $T_L$          | 260                                                                | $^\circ\text{C}$ |
| Gate-Source ESD Rating<br>(HBM, Method 3015)                              | ESD            | 2000                                                               | V                |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


1. Surface-mounted on FR4 board using 1 sq in pad size with 1 oz Cu.
2. Surface-mounted on FR4 board using 0.08 sq in pad size with 1 oz Cu.

| $V_{(BR)DSS}$ | $R_{DS(on)}$ MAX     | $I_D$ MAX |
|---------------|----------------------|-----------|
| 60 V          | 1.6 $\Omega$ @ 10 V  | 380 mA    |
|               | 2.5 $\Omega$ @ 4.5 V |           |


## SIMPLIFIED SCHEMATIC



## MARKING DIAGRAM & PIN ASSIGNMENT



**SOT-23  
CASE 318  
STYLE 21**



704 = Specific Device Code\*  
M = Date Code\*  
■ = Pb-Free Package

(Note: Microdot may be in either location)

\*Specific Device Code, Date Code or overbar orientation and/or location may vary depending upon manufacturing location. This is a representation only and actual devices may not match this drawing exactly.

## ORDERING INFORMATION

| Device                    | Package             | Shipping†          |
|---------------------------|---------------------|--------------------|
| 2N7002KT1G,<br>2V7002KT1G | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel |
| 2N7002KT7G                | SOT-23<br>(Pb-Free) | 3500 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# 2N7002K, 2V7002K

## THERMAL CHARACTERISTICS

| Characteristic                              | Symbol          | Max | Unit |
|---------------------------------------------|-----------------|-----|------|
| Junction-to-Ambient – Steady State (Note 3) | $R_{\theta JA}$ | 300 | °C/W |
| Junction-to-Ambient – $t \leq 5$ s (Note 3) |                 | 92  |      |
| Junction-to-Ambient – Steady State (Note 4) |                 | 417 |      |
| Junction-to-Ambient – $t \leq 5$ s (Note 4) |                 | 154 |      |

3. Surface-mounted on FR4 board using 1 sq in pad size with 1 oz Cu.

4. Surface-mounted on FR4 board using 0.08 sq in pad size with 1 oz Cu.

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test Condition | Min | Typ | Max | Unit |
|-----------|--------|----------------|-----|-----|-----|------|
|-----------|--------|----------------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|                                                           |                   |                                      |                           |    |          |         |
|-----------------------------------------------------------|-------------------|--------------------------------------|---------------------------|----|----------|---------|
| Drain-to-Source Breakdown Voltage                         | $V_{(BR)DSS}$     | $V_{GS} = 0$ V, $I_D = 250$ $\mu$ A  | 60                        |    |          | V       |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | $V_{(BR)DSS}/T_J$ |                                      |                           | 71 |          | mV/°C   |
| Zero Gate Voltage Drain Current                           | $I_{DSS}$         | $V_{GS} = 0$ V,<br>$V_{DS} = 60$ V   | $T_J = 25^\circ\text{C}$  |    | 1        | $\mu$ A |
|                                                           |                   |                                      | $T_J = 125^\circ\text{C}$ |    | 10       |         |
|                                                           |                   | $V_{GS} = 0$ V,<br>$V_{DS} = 50$ V   | $T_J = 25^\circ\text{C}$  |    | 100      | nA      |
|                                                           |                   |                                      |                           |    |          |         |
| Gate-to-Source Leakage Current                            | $I_{GSS}$         | $V_{DS} = 0$ V, $V_{GS} = \pm 20$ V  |                           |    | $\pm 10$ | $\mu$ A |
|                                                           |                   | $V_{DS} = 0$ V, $V_{GS} = \pm 10$ V  |                           |    | 450      | nA      |
|                                                           |                   | $V_{DS} = 0$ V, $V_{GS} = \pm 5.0$ V |                           |    | 150      | nA      |

### ON CHARACTERISTICS (Note 5)

|                                            |                  |                                         |     |      |     |          |
|--------------------------------------------|------------------|-----------------------------------------|-----|------|-----|----------|
| Gate Threshold Voltage                     | $V_{GS(TH)}$     | $V_{GS} = V_{DS}$ , $I_D = 250$ $\mu$ A | 1.0 |      | 2.3 | V        |
| Negative Threshold Temperature Coefficient | $V_{GS(TH)}/T_J$ |                                         |     | 4.0  |     | mV/°C    |
| Drain-to-Source On Resistance              | $R_{DS(on)}$     | $V_{GS} = 10$ V, $I_D = 500$ mA         |     | 1.19 | 1.6 | $\Omega$ |
|                                            |                  | $V_{GS} = 4.5$ V, $I_D = 200$ mA        |     | 1.33 | 2.5 |          |
| Forward Transconductance                   | $g_{FS}$         | $V_{DS} = 5$ V, $I_D = 200$ mA          |     | 530  |     | mS       |

### CHARGES AND CAPACITANCES

|                              |              |                                                      |  |      |     |    |
|------------------------------|--------------|------------------------------------------------------|--|------|-----|----|
| Input Capacitance            | $C_{ISS}$    | $V_{GS} = 0$ V, $f = 1$ MHz,<br>$V_{DS} = 20$ V      |  | 24.5 | 45  | pF |
| Output Capacitance           | $C_{OSS}$    |                                                      |  | 4.2  | 8.0 |    |
| Reverse Transfer Capacitance | $C_{RSS}$    |                                                      |  | 2.2  | 5.0 |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 4.5$ V, $V_{DS} = 10$ V;<br>$I_D = 200$ mA |  | 0.7  |     | nC |
| Threshold Gate Charge        | $Q_{G(TH)}$  |                                                      |  | 0.1  |     |    |
| Gate-to-Source Charge        | $Q_{GS}$     |                                                      |  | 0.3  |     |    |
| Gate-to-Drain Charge         | $Q_{GD}$     |                                                      |  | 0.1  |     |    |

### SWITCHING CHARACTERISTICS, $V_{GS} = V$ (Note 6)

|                     |              |                                                                          |  |      |  |    |
|---------------------|--------------|--------------------------------------------------------------------------|--|------|--|----|
| Turn-On Delay Time  | $t_{d(ON)}$  | $V_{GS} = 10$ V, $V_{DD} = 25$ V,<br>$I_D = 500$ mA, $R_G = 25$ $\Omega$ |  | 12.2 |  | ns |
| Rise Time           | $t_r$        |                                                                          |  | 9.0  |  |    |
| Turn-Off Delay Time | $t_{d(OFF)}$ |                                                                          |  | 55.8 |  |    |
| Fall Time           | $t_f$        |                                                                          |  | 29   |  |    |

### DRAIN-SOURCE DIODE CHARACTERISTICS

|                       |          |                                   |                          |  |     |     |   |
|-----------------------|----------|-----------------------------------|--------------------------|--|-----|-----|---|
| Forward Diode Voltage | $V_{SD}$ | $V_{GS} = 0$ V,<br>$I_S = 200$ mA | $T_J = 25^\circ\text{C}$ |  | 0.8 | 1.2 | V |
|                       |          |                                   | $T_J = 85^\circ\text{C}$ |  | 0.7 |     |   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. Pulse Test: pulse width  $\leq 300$   $\mu$ s, duty cycle  $\leq 2\%$

6. Switching characteristics are independent of operating junction temperatures

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Temperature




Figure 4. On-Resistance vs. Drain Current and Temperature




Figure 5. On-Resistance vs. Gate-to-Source Voltage




Figure 6. On-Resistance Variation with Temperature

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 9. Diode Forward Voltage vs. Current




Figure 10. Threshold Voltage with Temperature

# 2N7002K, 2V7002K

## TYPICAL CHARACTERISTICS




Figure 11. Thermal Response – 1 sq in pad




Figure 12. Thermal Response – minimum pad

# MECHANICAL CASE OUTLINE

## PACKAGE DIMENSIONS

ON Semiconductor®



### SOT-23 (TO-236) CASE 318-08 ISSUE AS

DATE 30 JAN 2018

SCALE 4:1



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.


| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 0.89        | 1.00 | 1.11 | 0.035  | 0.039 | 0.044 |
| A1  | 0.01        | 0.06 | 0.10 | 0.000  | 0.002 | 0.004 |
| b   | 0.37        | 0.44 | 0.50 | 0.015  | 0.017 | 0.020 |
| c   | 0.08        | 0.14 | 0.20 | 0.003  | 0.006 | 0.008 |
| D   | 2.80        | 2.90 | 3.04 | 0.110  | 0.114 | 0.120 |
| E   | 1.20        | 1.30 | 1.40 | 0.047  | 0.051 | 0.055 |
| e   | 1.78        | 1.90 | 2.04 | 0.070  | 0.075 | 0.080 |
| L   | 0.30        | 0.43 | 0.55 | 0.012  | 0.017 | 0.022 |
| L1  | 0.35        | 0.54 | 0.69 | 0.014  | 0.021 | 0.027 |
| HE  | 2.10        | 2.40 | 2.64 | 0.083  | 0.094 | 0.104 |
| T   | 0°          | ---  | 10°  | 0°     | ---   | 10°   |

#### GENERIC MARKING DIAGRAM\*



XXX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

#### RECOMMENDED SOLDERING FOOTPRINT



\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

STYLE 1 THRU 5:  
CANCELLED

STYLE 6:  
PIN 1. BASE  
2. EMITTER  
3. COLLECTOR

STYLE 7:  
PIN 1. EMITTER  
2. BASE  
3. COLLECTOR

STYLE 8:  
PIN 1. ANODE  
2. NO CONNECTION  
3. CATHODE

STYLE 9:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 10:  
PIN 1. DRAIN  
2. SOURCE  
3. GATE

STYLE 11:  
PIN 1. ANODE  
2. CATHODE  
3. CATHODE-ANODE

STYLE 12:  
PIN 1. CATHODE  
2. CATHODE  
3. ANODE

STYLE 13:  
PIN 1. SOURCE  
2. DRAIN  
3. GATE

STYLE 14:  
PIN 1. CATHODE  
2. GATE  
3. ANODE

STYLE 15:  
PIN 1. GATE  
2. CATHODE  
3. ANODE

STYLE 16:  
PIN 1. ANODE  
2. CATHODE  
3. CATHODE

STYLE 17:  
PIN 1. NO CONNECTION  
2. ANODE  
3. CATHODE

STYLE 18:  
PIN 1. NO CONNECTION  
2. CATHODE  
3. ANODE

STYLE 19:  
PIN 1. CATHODE  
2. ANODE  
3. CATHODE-ANODE

STYLE 20:  
PIN 1. CATHODE  
2. ANODE  
3. GATE

STYLE 21:  
PIN 1. GATE  
2. SOURCE  
3. DRAIN

STYLE 22:  
PIN 1. RETURN  
2. OUTPUT  
3. INPUT

STYLE 23:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 24:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE

STYLE 25:  
PIN 1. ANODE  
2. CATHODE  
3. GATE

STYLE 26:  
PIN 1. CATHODE  
2. ANODE  
3. NO CONNECTION

STYLE 27:  
PIN 1. CATHODE  
2. CATHODE  
3. CATHODE

STYLE 28:  
PIN 1. ANODE  
2. ANODE  
3. ANODE

|                         |                        |                                                                                                                                                                                  |
|-------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42226B</b>     | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOT-23 (TO-236)</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**onsemi Website:** [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

**North American Technical Support:**

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

**Europe, Middle East and Africa Technical Support:**

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative