





# EDZ 950



2-24 poles, Spacing 5.08 mm  
insert required no. of poles \*\*  
How to order see page 6

## Ratings:

	 UL1059	 CSA 22.2 No. 158	 DIN VDE 0627
<b>Rated Voltage</b>	<b>250 VB</b>	<b>300 VB</b>	<b>250 V</b>
<b>Rated Current</b>	<b>15 A</b>	<b>16 A</b>	<b>12 A (T60)</b>
<b>Wire Size</b>	<b>AWG 22-12</b>	<b>AWG 22-14</b>	<b>2.5 mm<sup>2</sup></b>
<b>Test Voltage</b>			<b>2.21 kV</b>
<b>Rated Torque/Screw Size</b>			<b>0.5 Nm/M3</b>

## Rated Cross Section

Single Wire (solid)	2.5 mm <sup>2</sup>
Stranded Wire (flexible)	2.5 mm <sup>2</sup>
Stranded wire with Ferrules	2.5 mm <sup>2</sup>

## Dimensions

Spacing	5.08 mm
Stripped Length	6.0 mm

## Materials

Insulating Material	PA
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Contact	CuZn
Wire Guard	CuSn
Color	Green

