

Reducing bridge - RB UT 16-(2,5/4) - 3047073

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Reducing bridge, Number of positions: 1, Color: red

Product Features

- Tested for railway applications

Key commercial data

Packing unit	1 PCE
Minimum order quantity	10 PCE
GTIN	 4 046356 055864
Custom tariff number	85389099
Country of origin	POLAND

Technical data

Technical data

Color	red
Material	PA 6.6
Number of positions	1
Inflammability class according to UL 94	V0
Maximum temperature	125 °C

Classifications

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489

Reducing bridge - RB UT 16-(2,5/4) - 3047073

Classifications

UNSPSC

UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426
UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141140
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140