

Screw flange - UT 6-QUATTRO/2P-F



3060843

<https://www.phoenixcontact.com/de/produkte/3060843>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Screw flange, mounting type: NS 35/7,5, NS 35/15, color: gray



Commercial Data

Item number	3060843
Packing unit	50 pc
Minimum order quantity	50 pc
Sales Key	A1 - Reihenklemmen
Product Key	BE114Z
Catalog Page	Page 373 (C-1-2019)
GTIN	4046356608176
Weight per Piece (including packing)	13 g
Weight per Piece (excluding packing)	13 g
Customs tariff number	85369010
Country of origin	CN

Screw flange - UT 6-QUATTRO/2P-F



3060843

<https://www.phoenixcontact.com/de/produkte/3060843>

Technical Data

Product properties

Product type	Flange
--------------	--------

Connection data

Screw thread	M2,5
Tightening torque	0.4 ... 0.5 Nm

Dimensions

Width	8.2 mm
Height NS 35/15	67.5 mm
Height NS 35/7,5	60 mm
Length	86.5 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	NS 35/7,5
---------------	-----------

Screw flange - UT 6-QUATTRO/2P-F

3060843

<https://www.phoenixcontact.com/de/produkte/3060843>



NS 35/15

Screw flange - UT 6-QUATTRO/2P-F



3060843

<https://www.phoenixcontact.com/de/produkte/3060843>

Classifications

ECLASS

ECLASS-9.0	27141135
ECLASS-10.0.1	27141135
ECLASS-11.0	27141135

ETIM

ETIM 8.0	EC001041
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Screw flange - UT 6-QUATTRO/2P-F



3060843

<https://www.phoenixcontact.com/de/produkte/3060843>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de