

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [31073-1071](#)
Status: **Active**
Overview: H-DAC™ 64 Single Row
Description: 2.54mm H-DAC 64™, 6 Way Male Housing Assembly, Single Row, Polarization B, with Xmas Tree Attachment

Documents:

[3D Model](#) [Application Specification AS-31067-100 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Product Specification PS-31067-0001 \(PDF\)](#)

General

Product Family	Crimp Housings
Series	31073
Application	Power, Wire-to-Wire
Comments	Polarization Option B, Gray
Overview	H-DAC™ 64 Single Row
Product Name	H-DAC 64™
UPC	756054393154

Physical

Circuits (maximum)	6
Circuits Detail	6
Color - Resin	Gray
Gender	Male
Glow-Wire Compliant	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Modified Polystyrene, Polyester
Net Weight	3.024/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	2.54mm
Polarized to Mating Part	Yes
Ports	1
Stackable	No
Temperature Range - Operating	-40°C to +100°C


Electrical

Current - Maximum per Contact	11A, 9A
-------------------------------	---------

Material Info

Reference - Drawing Numbers

Application Specification	AS-31067-100
Product Specification	PS-31067-0001
Sales Drawing	SD-31110-003



EU RoHS

ELV and RoHS Compliant
REACH SVHC
 Not Reviewed
Low-Halogen Status
Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[31073Series](#)

Mates With

HDAC 64™, 6 Way Receptacle Assembly
[310731011](#)

Use With

See Product Spec