

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0313872034](#)  
**Status:** **Active**  
**Overview:** [MX123 Sealed Connection System](#)  
**Description:** 2.54mm Pitch, MX123 Header, 73 Circuits Shrouded Assembly, Qty(72) 0.64mm Square Signal Pins + Qty(1) 2.8mm Power Blade, Harness Side Key Code A, Black (Ag Mate Side Finish)

**Documents:**

<a href="#">3D Model</a>	<a href="#">Packaging Specification PK-31301-916 (PDF)</a>
<a href="#">3D Model (PDF)</a>	<a href="#">Test Summary TS-31387-1658-001 (PDF)</a>
<a href="#">Drawing (PDF)</a>	<a href="#">Datasheet (PDF)</a>
<a href="#">Product Specification PS-31387-200-001 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>
<a href="#">Application Specification AS-31386-200-001 (PDF)</a>	

**General**

Product Family	PCB Headers
Series	<a href="#">31387</a>
Application	Automotive, Power, Wire-to-Board
Overview	<a href="#">MX123 Sealed Connection System</a>
Product Name	MX123
UPC	884982908864

**Physical**


Breakaway	No
Circuits (Loaded)	73
Circuits (maximum)	73
Color - Resin	Black
First Mate / Last Break	No
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Plating Mating	Silver
Material - Plating Termination	Tin
Net Weight	23.220/g
Number of Rows	4
Orientation	Vertical
PC Tail Length	6.50mm
PCB Locator	No
PCB Retention	None
Packaging Type	Carton
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	2.54mm
Polarized to Mating Part	Yes
Polarized to PCB	No
Shrouded	Yes
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-40° to +125°C
Termination Interface: Style	Through Hole

**Electrical**

Current - Maximum per Contact	11.0A
Voltage - Maximum	500V

**Solder Process Data**

Lead-freeProcess Capability	N/A
-----------------------------	-----



**EU ELV**

**Compliant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2020)4578-DC (25  
June 2020)

**Halogen-Free**

**Status**

**Not Relevant**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Not Relevant

Compliant

Not Contained

**Search Parts in this Series**

[31387 Series](#)

**Mates With**

[MX123 Female Harness Connector Assembly 34566](#)

**Use With**

[34736 MX64 Female Terminals Ag](#)

**Material Info**

**Reference - Drawing Numbers**

Application Specification	AS-31386-200-001
Packaging Specification	PK-31301-916
Product Specification	PS-31387-200-001
Sales Drawing	SD-31387-073-000, SD-31387-173-000
Test Summary	TS-31387-1658-001

This document was generated on 09/28/2020

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**