

3156 00530006

(Home : Products : Sensors : Thermostats : 3156)



3156 Series Low Silhouette Hermetic Thermostats

Actual product appearance may vary.

Sales & Service Distributor Inventory

Specs

Product Specifications

Functional Properties	Close on rise
Reset Type	Automatic
Amperage	100 mA/500 mA
Voltage	120 Vac/50 Vdc
Operating Temperature	-29 °C to 177 °C [-20 °F to 350 °F]
Environmental Exposure Range	-54 °C to 260 °C [-65 °F to 500 °F]
Open Temperature	101.7 °C [215 °F]
Close Temperature	45.0 °C [113 °F]
Open Tolerance	2.8 °C [5 °F]
Close Tolerance	2.8 °C [5 °F]
Dielectric Strength	MIL-STD-202, Method 301; 750 Vac 60 Hz - Terminal to Case
Insulation Resistance	MIL-STD-202, Method 302; Cond. B - 500 MOhm - 500 Vdc applied
Contact Resistance	MIL-STD-202, Method 307; 0.050 Ohm
Hermetic Seal	MIL-STD-202, Method 112; Cond. 1x10-5
Moisture Resistance	MIL-STD-202, Method 106
Housing Material	Steel housing hermetically sealed with glass-to-metal seal at terminal junction
Contact Material	WE -1 gold alloy cross point
Mounting	B210 fixed bracket
Series Name	3156

Product Search

Product Type: All Product Types

New Products Only

Industry: All Industries

Entire Product Catalog

Search Term: Start Here ...

Search

Distributor Inventory

Input part number for stock availability

Narrow Your Search

Modify Your Search

Products

Select Option

Technology

Select Option

Industries Served

Select Option

eCOM Login
Request Access to eCOM
Rep/AD Portal Login
Rep/AD Portal Access Request
Sample Request
Digital University Login
Limitless Microsite
Supplier Microsite

Application Demos
White Papers
Application Notes
Literature Request
Data Sheets
Videos

Customer Service
Technical Support
Global Sales & Service
Website Feedback

