Cable lug - C-BCSI 1,5/9X2,8

3240531

https://www.phoenixcontact.com/pc/products/3240531

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Flat pin cable lug, red, 0.5 - 1.5 mm^2, pin dimensions: 20 x 2.8 mm

Your advantages

- Hard-soldered crimping zone for maximum conductor pull-out forces in connection with CRIMPFOX RCI... pliers
- Easy and reliable conductor entry thanks to 'EASY ENTRY'
- Halogen-free
- Electrogalvanized

Commercial Data

Item number	3240531
Packing unit	100 pc
Minimum order quantity	100 pc
Product Key	BH3461
Catalog Page	Page 497 (C-3-2019)
GTIN	4046356528016
Weight per Piece (including packing)	0.589 g
Weight per Piece (excluding packing)	0.589 g
Customs tariff number	85369010
Country of origin	CN

Technical Data


Product properties

Product type	Connector

Electrical properties

Fuse	no

Dimensions

Dimensional drawing	
Width	2.8 mm
Length	19.5 mm
Length of the insulating material sleeve	10.5 mm
Length contact range	9 mm
Maximum stripping length	7 mm
Min. material thickness	0.75 mm
Inner dimensions of the insulating collar	4.1 mm

Material specifications

Color	red
Material	CU
Flammability rating according to UL 94	V2
Coating	electrogalvanized
Insulating material	PA
Components	halogen-free


Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 105 °C
Permanent temperature	105 °C
Short-term temperature	120 °C

Drawings

Dimensional drawing



Classifications

ECLASS

ECLASS-9.0	27400204
ECLASS-10.0.1	27400204
ECLASS-11.0	27400204

ETIM

ETIM 8.0	EC001052

UNSPSC

UNSPSC 21.0	27121700

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com