

WT-STEEL SH 7,9X679 - Cable tie

3240830

<https://www.phoenixcontact.com/de/produkte/3240830>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening

Commercial Data

| | |
|--------------------------------------|-------------------------|
| Item number | 3240830 |
| Packing unit | 100 pc |
| Minimum order quantity | 100 pc |
| Sales Key | B1 - Markierung Montage |
| Product Key | BE7132 |
| Catalog Page | Page 621 (C-3-2019) |
| GTIN | 4046356705783 |
| Weight per Piece (including packing) | 99,99 g |
| Weight per Piece (excluding packing) | 12,9 g |
| Customs tariff number | 73269098 |
| Country of origin | GB |

WT-STEEL SH 7,9X679 - Cable tie



3240830

<https://www.phoenixcontact.com/de/produkte/3240830>

Technical Data

Product properties

| | |
|----------------------|-------------|
| Product type | Cable tie |
| Type | Steel strip |
| Tensile strength GRP | 1335 N |

Dimensions

| | |
|-------------------------|---------|
| Width | 7.9 mm |
| Length | 679 mm |
| Max. material thickness | 0.25 mm |

Material specifications

| | |
|------------|---------------------------------|
| Color | silver |
| Material | Stainless steel 1.4401/AISI 316 |
| Components | free from silicone and halogen |

Cable/line

| | |
|-------------------------|----------|
| External cable diameter | ≤ 203 mm |
| Tensile strength | 1335 N |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -80 °C ... 538 °C |
| Ambient temperature (assembly) | -80 °C ... 538 °C |
| Resistance to UV radiation | yes |

Standards and regulations

| | |
|----------------------------|-----|
| Resistance to UV radiation | yes |
|----------------------------|-----|

Mounting

| | |
|---------------|-------------------|
| Mounting type | Cannot be removed |
|---------------|-------------------|

WT-STEEL SH 7,9X679 - Cable tie



3240830

<https://www.phoenixcontact.com/de/produkte/3240830>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/de/produkte/3240830>



LR



UL Listed

Approval ID: E328576



cUL Listed

Approval ID: E328576

WT-STEEL SH 7,9X679 - Cable tie



3240830

<https://www.phoenixcontact.com/de/produkte/3240830>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27140702 |
| ECLASS-12.0 | 27140702 |
| ECLASS-13.0 | 27140702 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000046 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121700 |
|-------------|----------|

WT-STEEL SH 7,9X679 - Cable tie



3240830

<https://www.phoenixcontact.com/de/produkte/3240830>

Environmental Product Compliance

| | |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

WT-STEEL SH 7,9X679 - Cable tie

3240830

<https://www.phoenixcontact.com/de/produkte/3240830>



Accessories

UNIFOX-CT M 7,9 - Cable tie tool

1212610

<https://www.phoenixcontact.com/de/produkte/1212610>



Cable binder pliers, for steel cable binders with a width of up to 7.9 mm, for a material thickness of up to 0.3 mm

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de