


# Type 325/326, -55 °C to 125 °C Long-Life, Switching Power Grade Radial

## High Temperature and Ultra-Low ESR



Type 325



Type 326

The Types 325 and 326 are the ultra-wide-temperature, low-ESR capacitors for switching power-supply outputs and automotive applications. The 125 °C capability and exceptionally low ESRs enable high ripple-current capability. With series inductance of 12 to 16 nH and ripple currents to 27 amps one of these capacitors can save by replacing eight to ten of the 12.5 mm diameter capacitors routinely at the output of switching power supplies. Type 325 has three leads for rugged, reverse-proof mounting, and Type 326 has two leads.

### Highlights

- 2000 hour life test at 125 °C
- Ripple Current to 27 amps
- ESRs to 5 mΩ
- > 90% capacitance at -40 °C
- Replaces multiple capacitors

### RoHS Compliant

### Specifications

**Operating Temperature:**

-55 °C to 125 °C

**Rated Voltage:**

6.3 to 63 Vdc –

**Capacitance:**

880 μF to 46,000 μF

**Capacitance Tolerance:**

-10 +75%

**Leakage Current:**

≤0.5  $\sqrt{CV}$  μA, 4 mA max, 5 minutes

**Cold Impedance:**

-55 °C multiple of 25 °C Z ≤2.5 @ 120 Hz  
≤20 from 20–100 kHz

**Ripple Current Multipliers:**

### Ambient Temperature

| 45°C | 55°C | 65°C | 75°C | 85°C | 95°C | 105°C | 115°C | 125°C |
|------|------|------|------|------|------|-------|-------|-------|
| 1.39 | 1.3  | 1.21 | 1.11 | 1.00 | 0.88 | 0.73  | 0.55  | 0.26  |

### Frequency

| 120 Hz      | 360 Hz | 400 Hz | 1 kHz | 20-100 kHz |
|-------------|--------|--------|-------|------------|
| see ratings | 0.76   | 0.77   | 0.85  | 1.00       |

**Life Test:**

2000 h with rated voltage at 125 °C

Δ capacitance ± 10%

ESR 125 % of limit

DCL 100 % of limit

**Load Life:**

4000 h at full load at 85 °C

Δ capacitance ± 10%

ESR 200 % of limit

DCL 100 % of limit

**Shelf Life:**

500 h at 105 °C,

Δ capacitance ± 10%,



ESR 110% of limit,

DCL 200% of limit

**Vibration:**

10 to 55 Hz, 0.06" and 10 g max, 2 h each plane

### Outline Drawings



# Type 325/326, -55 °C to 125 °C Long-Life, Switching Power Grade Radial

| Case<br>Code                   | Insulated          |                           | Bare Can           |                | Lead Spacing |                | Lead Diameter |    |
|--------------------------------|--------------------|---------------------------|--------------------|----------------|--------------|----------------|---------------|----|
|                                | D ± 0.015 (0.4 mm) | Epoxy<br>endseal L<br>Max | D ± 0.015 (0.4 mm) | Type 325       | Type 326     | dia.           | AWG           |    |
|                                | L ± 0.062 (1.6 mm) |                           | L ± 0.030 (0.8 mm) | S1             | T            | S2             |               |    |
|                                | D x L              |                           | D x L              | ±0.020(0.5 mm) |              | ±0.020(0.5 mm) |               |    |
| Case Dimensions in Inches      |                    |                           |                    |                |              |                |               |    |
| GE                             | .765 x 1.150       | 1.212                     | 0.750 x 1.125      | 0.200          | 0.300        | 0.300          | 0.040         | 18 |
| GJ                             | .765 x 1.650       | 1.712                     | 0.750 x 1.625      | 0.200          | 0.300        | 0.300          | 0.040         | 18 |
| GL                             | .765 x 2.150       | 2.212                     | 0.750 x 2.125      | 0.200          | 0.300        | 0.300          | 0.040         | 18 |
| GP                             | .765 x 2.650       | 2.712                     | 0.750 x 2.625      | 0.200          | 0.300        | 0.300          | 0.040         | 18 |
| GS                             | .765 x 3.150       | 3.212                     | 0.750 x 3.125      | 0.200          | 0.300        | 0.300          | 0.040         | 18 |
| GT                             | .765 x 3.650       | 3.712                     | 0.750 x 3.625      | 0.200          | 0.300        | 0.300          | 0.040         | 18 |
| HE                             | .890 x 1.150       | 1.212                     | 0.875 x 1.125      | 0.300          | 0.400        | 0.300          | 0.040         | 18 |
| HJ                             | .890 x 1.650       | 1.712                     | 0.875 x 1.625      | 0.300          | 0.400        | 0.300          | 0.040         | 18 |
| HL                             | .890 x 2.150       | 2.212                     | 0.875 x 2.125      | 0.300          | 0.400        | 0.300          | 0.040         | 18 |
| HP                             | .890 x 2.650       | 2.712                     | 0.875 x 2.625      | 0.300          | 0.400        | 0.300          | 0.040         | 18 |
| HS                             | .890 x 3.150       | 3.212                     | 0.875 x 3.125      | 0.300          | 0.400        | 0.300          | 0.040         | 18 |
| HT                             | .890 x 3.650       | 3.712                     | 0.875 x 3.625      | 0.300          | 0.400        | 0.300          | 0.040         | 18 |
| JE                             | 1.015 x 1.150      | 1.212                     | 1.000 x 1.125      | 0.300          | 0.400        | 0.400          | 0.040         | 18 |
| JJ                             | 1.015 x 1.650      | 1.712                     | 1.000 x 1.625      | 0.300          | 0.400        | 0.400          | 0.040         | 18 |
| JL                             | 1.015 x 2.150      | 2.212                     | 1.000 x 2.125      | 0.300          | 0.400        | 0.400          | 0.040         | 18 |
| JP                             | 1.015 x 2.650      | 2.712                     | 1.000 x 2.625      | 0.300          | 0.400        | 0.400          | 0.040         | 18 |
| JS                             | 1.015 x 3.150      | 3.212                     | 1.000 x 3.125      | 0.300          | 0.400        | 0.400          | 0.040         | 18 |
| JT                             | 1.015 x 3.650      | 3.712                     | 1.000 x 3.625      | 0.300          | 0.400        | 0.400          | 0.040         | 18 |
| Case Dimensions in Millimeters |                    |                           |                    |                |              |                |               |    |
| GE                             | 19.4 x 29.2        | 30.8                      | 19.1 x 28.6        | 5.08           | 7.62         | 7.62           | 1.02          | 18 |
| GJ                             | 19.4 x 41.9        | 43.5                      | 19.1 x 41.3        | 5.08           | 7.62         | 7.62           | 1.02          | 18 |
| GL                             | 19.4 x 54.6        | 56.2                      | 19.1 x 54.0        | 5.08           | 7.62         | 7.62           | 1.02          | 18 |
| GP                             | 19.4 x 67.3        | 68.9                      | 19.1 x 66.7        | 5.08           | 7.62         | 7.62           | 1.02          | 18 |
| GS                             | 19.4 x 80.0        | 81.6                      | 19.1 x 79.4        | 5.08           | 7.62         | 7.62           | 1.02          | 18 |
| GT                             | 19.4 x 92.7        | 94.3                      | 19.1 x 92.1        | 5.08           | 7.62         | 7.62           | 1.02          | 18 |
| HE                             | 22.6 x 29.2        | 30.8                      | 22.2 x 28.6        | 7.62           | 10.16        | 7.62           | 1.02          | 18 |
| HJ                             | 22.6 x 41.9        | 43.5                      | 22.2 x 41.3        | 7.62           | 10.16        | 7.62           | 1.02          | 18 |
| HL                             | 22.6 x 54.6        | 56.2                      | 22.2 x 54.0        | 7.62           | 10.16        | 7.62           | 1.02          | 18 |
| HP                             | 22.6 x 67.3        | 68.9                      | 22.2 x 66.7        | 7.62           | 10.16        | 7.62           | 1.02          | 18 |
| HS                             | 22.6 x 80.0        | 81.6                      | 22.2 x 79.4        | 7.62           | 10.16        | 7.62           | 1.02          | 18 |
| HT                             | 22.6 x 92.7        | 94.3                      | 22.2 x 92.1        | 7.62           | 10.16        | 7.62           | 1.02          | 18 |
| JE                             | 25.8 x 29.2        | 30.8                      | 25.4 x 28.6        | 7.62           | 10.16        | 10.16          | 1.02          | 18 |
| JJ                             | 25.8 x 41.9        | 43.5                      | 25.4 x 41.3        | 7.62           | 10.16        | 10.16          | 1.02          | 18 |
| HL                             | 25.8 x 54.6        | 56.2                      | 25.4 x 54.0        | 7.62           | 10.16        | 10.16          | 1.02          | 18 |
| JP                             | 25.8 x 67.3        | 68.9                      | 25.4 x 66.7        | 7.62           | 10.16        | 10.16          | 1.02          | 18 |
| JS                             | 25.8 x 80.0        | 81.6                      | 25.4 x 79.4        | 7.62           | 10.16        | 10.16          | 1.02          | 18 |
| JT                             | 25.8 x 92.7        | 94.3                      | 25.4 x 92.1        | 7.62           | 10.16        | 10.16          | 1.02          | 18 |


## Part Numbering System

|                         |              |               |            |           |               |                   |
|-------------------------|--------------|---------------|------------|-----------|---------------|-------------------|
| <b>325</b>              | <b>393</b>   | <b>U</b>      | <b>6R3</b> | <b>JS</b> | <b>1</b>      | <b>E</b>          |
| Type                    | Capacitance  | Tolerance     | Voltage    | Case Code | Insulation    | Epoxy             |
| 325 - 3 leads           | 152=1500 µF  | M = 20%       | 6R3=6.3 V  | See       | 0 = bare can  | (blank) =no epoxy |
| 326 - 2 leads           | 393=39000 µF | T = 10% + 50% | 035=35 V   | Ratings   | 1 = polyester | E = Epoxy endseal |
| 326A - 3 leads, laydown |              | U = 10% + 75% |            |           |               |                   |


# Type 325/326, -55 °C to 125 °C Long-Life, Switching Power Grade Radial

## Typical Performance Curves


Type 325 Capacitance vs Temperature & Frequency, 10000  $\mu$ F, 16 V




Type 325 ESR vs Temperature and Frequency, 10000  $\mu$ F, 16 V




Type 325 Impedance vs Temperature and Frequency, 10000  $\mu$ F, 16 V




Type 325 Capacitance vs Temperature & Frequency, 5600  $\mu$ F, 25 V




Type 325 ESR vs Temperature and Frequency, 5600  $\mu$ F, 25 V




Type 325 Impedance vs Temperature and Frequency, 5600  $\mu$ F, 25 V



Type 325 Capacitance vs Temperature & Frequency, 3900  $\mu$ F, 35 V



Type 325 ESR vs Temperature and Frequency, 3900  $\mu$ F, 35 V



# Type 325/326, -55 °C to 125 °C Long-Life, Switching Power Grade Radial Ratings

| Cap.<br>(μF)          | Catalog<br>Part Number | ESR MAX<br>@ 25°C     |                      | Ripple MAX<br>@ 85°C |                      | Nom Size<br>Insulated<br>D X L<br>(in) |
|-----------------------|------------------------|-----------------------|----------------------|----------------------|----------------------|----------------------------------------|
|                       |                        | 120 Hz 20 kHz<br>(mΩ) | 120 Hz 20 kHz<br>(A) | 120 Hz 20 kHz<br>(A) | 120 Hz 20 kHz<br>(A) |                                        |
| 6.3 Vdc (8 Vdc Surge) |                        |                       |                      |                      |                      |                                        |
| 4400                  | 325442U6R3GE1          | 65.7                  | 36.2                 | 3.95                 | 5.31                 | 0.77 X 1.15                            |
| 5800                  | 325582U6R3HE1          | 42.8                  | 26.0                 | 5.37                 | 6.89                 | 0.89 X 1.15                            |
| 7100                  | 325712U6R3GJ1          | 41.9                  | 23.5                 | 5.68                 | 7.59                 | 0.77 X 1.65                            |
| 7700                  | 325772U6R3JE1          | 28.5                  | 17.2                 | 7.16                 | 9.22                 | 1.02 X 1.15                            |
| 11000                 | 325113U6R3GL1          | 29.5                  | 16.2                 | 7.56                 | 10.21                | 0.77 X 2.15                            |
| 12000                 | 325123U6R3HJ1          | 26.5                  | 14.7                 | 7.81                 | 10.51                | 0.89 X 1.65                            |
| 14000                 | 325143U6R3GP1          | 20.9                  | 13.6                 | 9.85                 | 12.21                | 0.77 X 2.65                            |
| 15000                 | 325153U6R3JJ1          | 16.2                  | 11.1                 | 10.88                | 13.13                | 1.02 X 1.65                            |
| 17000                 | 325173U6R3HL1          | 18.7                  | 11.0                 | 10.46                | 13.60                | 0.89 X 2.15                            |
| 18000                 | 325183U6R3GS1          | 18.1                  | 11.6                 | 11.42                | 14.23                | 0.77 X 3.15                            |
| 21000                 | 325213U6R3GT1          | 16.5                  | 10.6                 | 12.75                | 15.94                | 0.77 X 3.65                            |
| 23000                 | 325233U6R3HP1          | 14.3                  | 8.6                  | 13.02                | 16.81                | 0.89 X 2.65                            |
| 23000                 | 325233U6R3JL1          | 14.3                  | 8.7                  | 12.86                | 16.51                | 1.02 X 2.15                            |
| 29000                 | 325293U6R3HS1          | 10.5                  | 7.4                  | 16.40                | 19.48                | 0.89 X 3.15                            |
| 31000                 | 325313U6R3JP1          | 10.5                  | 7.3                  | 16.40                | 19.61                | 1.02 X 2.65                            |
| 35000                 | 325353U6R3HT1          | 10.1                  | 6.2                  | 17.75                | 22.70                | 0.89 X 3.65                            |
| 39000                 | 325393U6R3JS1          | 9.5                   | 6.3                  | 18.55                | 22.89                | 1.02 X 3.15                            |
| 46000                 | 325463U6R3JT1          | 8.3                   | 5.2                  | 21.23                | 26.70                | 1.02 X 3.65                            |
| 10 Vdc (13 Vdc Surge) |                        |                       |                      |                      |                      |                                        |
| 3300                  | 325332U010GE1          | 75.5                  | 36.2                 | 3.68                 | 5.31                 | 0.77 X 1.15                            |
| 4700                  | 325472U010HE1          | 42.8                  | 26.0                 | 5.37                 | 6.89                 | 0.89 X 1.15                            |
| 5400                  | 325542U010GJ1          | 42.7                  | 23.5                 | 5.63                 | 7.59                 | 0.77 X 1.65                            |
| 6400                  | 325642U010JE1          | 36.7                  | 17.2                 | 6.30                 | 9.22                 | 1.02 X 1.15                            |
| 8000                  | 325802U010GL1          | 31.4                  | 16.2                 | 7.33                 | 10.21                | 0.77 X 2.15                            |
| 9300                  | 325932U010HJ1          | 25.7                  | 14.7                 | 7.95                 | 10.51                | 0.89 X 1.65                            |
| 11000                 | 325113U010GP1          | 20.9                  | 13.6                 | 9.85                 | 12.21                | 0.77 X 2.65                            |
| 13000                 | 325133U010GS1          | 19                    | 11.6                 | 11.13                | 14.23                | 0.77 X 3.15                            |
| 13000                 | 325133U010JJ1          | 22.9                  | 11.1                 | 9.16                 | 13.13                | 1.02 X 1.65                            |
| 14000                 | 325143U010HL1          | 17.3                  | 11.0                 | 10.86                | 13.60                | 0.89 X 2.15                            |
| 16000                 | 325163U010GT1          | 17                    | 10.4                 | 12.57                | 16.08                | 0.77 X 3.65                            |
| 19000                 | 325193U010HP1          | 14.2                  | 8.6                  | 13.04                | 16.81                | 0.89 X 2.65                            |
| 19000                 | 325193U010JL1          | 16.2                  | 8.7                  | 12.10                | 16.51                | 1.02 X 2.15                            |
| 23000                 | 325233U010HS1          | 11.4                  | 7.4                  | 15.73                | 19.48                | 0.89 X 3.15                            |
| 26000                 | 325263U010JP1          | 11.4                  | 7.3                  | 15.73                | 19.61                | 1.02 X 2.65                            |
| 28000                 | 325283U010HT1          | 10.1                  | 6.2                  | 17.75                | 22.70                | 0.89 X 3.6                             |
| 32000                 | 325323U010JS1          | 10.5                  | 6.3                  | 17.69                | 22.89                | 1.02 X 3.15                            |
| 38000                 | 325383U010JT1          | 8.7                   | 5.2                  | 20.67                | 26.70                | 1.02 X 3.65                            |
| 16 Vdc (20 Vdc Surge) |                        |                       |                      |                      |                      |                                        |
| 2000                  | 325202U016GE1          | 92.6                  | 35.0                 | 3.33                 | 5.41                 | 0.77 X 1.15                            |
| 2800                  | 325282U016HE1          | 63.8                  | 26.0                 | 4.40                 | 6.89                 | 0.89 X 1.15                            |
| 3200                  | 325322U016GJ1          | 50.4                  | 23.5                 | 5.18                 | 7.59                 | 0.77 X 1.65                            |
| 3800                  | 325382U016JE1          | 48.6                  | 17.2                 | 5.48                 | 9.22                 | 1.02 X 1.15                            |
| 4800                  | 325482U016GL1          | 35.3                  | 16.2                 | 6.92                 | 10.21                | 0.77 X 2.15                            |
| 5600                  | 325562U016HJ1          | 32.2                  | 14.7                 | 7.09                 | 10.51                | 0.89 X 1.65                            |
| 6400                  | 325642U016GP1          | 26.6                  | 13.6                 | 8.73                 | 12.21                | 0.77 X 2.65                            |
| 7700                  | 325772U016JJ1          | 24.8                  | 11.1                 | 8.79                 | 13.13                | 1.02 X 1.65                            |
| 8000                  | 325802U016GS1          | 22.8                  | 11.6                 | 10.17                | 14.23                | 0.77 X 3.15                            |

| Cap.<br>(μF)                 | Catalog<br>Part Number | ESR MAX<br>@ 25°C<br>120 Hz 20 kHz<br>(mΩ) |      | Ripple MAX<br>@ 85°C<br>120 Hz 20 kHz<br>(A) |       | Nom Size<br>Insulated<br>D X L<br>(in) |
|------------------------------|------------------------|--------------------------------------------|------|----------------------------------------------|-------|----------------------------------------|
| 8400                         | 325842U016HL1          | 22.1                                       | 11.0 | 9.61                                         | 13.60 | 0.89 X 2.15                            |
| 9600                         | 325962U016GT1          | 24.8                                       | 10.1 | 10.41                                        | 16.28 | 0.77 X 3.65                            |
| 11000                        | 325113U016HP1          | 17.2                                       | 8.6  | 11.87                                        | 16.81 | 0.89 X 2.65                            |
| 12000                        | 325123U016JL1          | 17.2                                       | 8.7  | 11.74                                        | 16.51 | 1.02 X 2.15                            |
| 14000                        | 325143U016HS1          | 14.3                                       | 7.4  | 14.05                                        | 19.48 | 0.89 X 3.15                            |
| 15000                        | 325153U016JP1          | 13.3                                       | 7.3  | 14.55                                        | 19.61 | 1.02 X 2.65                            |
| 17000                        | 325173U016HT1          | 14.9                                       | 6.2  | 14.59                                        | 22.60 | 0.89 X 3.65                            |
| 19000                        | 325193U016JS1          | 11.4                                       | 6.3  | 16.92                                        | 22.89 | 1.02 X 3.15                            |
| 23000                        | 325233U016JT1          | 9.5                                        | 5.2  | 19.82                                        | 26.70 | 1.02 X 3.65                            |
| <b>25 Vdc (32 Vdc Surge)</b> |                        |                                            |      |                                              |       |                                        |
| 1300                         | 325132U025GE1          | 109.0                                      | 35.0 | 3.07                                         | 5.41  | 0.77 X 1.15                            |
| 1800                         | 325182U025HE1          | 70.8                                       | 26.0 | 4.17                                         | 6.89  | 0.89 X 1.15                            |
| 2100                         | 325212U025GJ1          | 55.1                                       | 23.5 | 4.96                                         | 7.59  | 0.77 X 1.65                            |
| 2500                         | 325252U025JE1          | 52.5                                       | 17.2 | 5.27                                         | 9.22  | 1.02 X 1.15                            |
| 3100                         | 325312U025GL1          | 38.0                                       | 16.2 | 6.66                                         | 10.21 | 0.77 X 2.15                            |
| 3600                         | 325362U025HJ1          | 35.0                                       | 14.7 | 6.80                                         | 10.51 | 0.89 X 1.65                            |
| 4100                         | 325412U025GP1          | 28.6                                       | 13.6 | 8.42                                         | 12.21 | 0.77 X 2.65                            |
| 4900                         | 325492U025JJ1          | 26.6                                       | 11.1 | 8.49                                         | 13.13 | 1.02 X 1.65                            |
| 5100                         | 325512U025GS1          | 24.8                                       | 11.6 | 9.76                                         | 14.23 | 0.77 X 3.15                            |
| 5400                         | 325542U025HL1          | 24.0                                       | 11.0 | 9.22                                         | 13.60 | 0.89 X 2.15                            |
| 6200                         | 325622U025GT1          | 24.8                                       | 10.1 | 10.41                                        | 16.28 | 0.77 X 3.65                            |
| 7200                         | 325722U025HP1          | 19.1                                       | 8.6  | 11.26                                        | 16.81 | 0.89 X 2.65                            |
| 7400                         | 325742U025JL1          | 19.1                                       | 8.7  | 11.13                                        | 16.51 | 1.02 X 2.15                            |
| 8900                         | 325892U025HS1          | 15.2                                       | 7.4  | 13.60                                        | 19.48 | 0.89 X 3.15                            |
| 9800                         | 325982U025JP1          | 15.3                                       | 7.3  | 13.60                                        | 19.61 | 1.02 X 2.65                            |
| 11000                        | 325113U025HT1          | 14.9                                       | 6.2  | 14.59                                        | 22.60 | 0.89 X 3.65                            |
| 12000                        | 325123U025JS1          | 12.4                                       | 6.3  | 16.27                                        | 22.89 | 1.02 X 3.15                            |
| 15000                        | 325153U025JT1          | 9.5                                        | 5.2  | 19.82                                        | 26.7  | 1.02 X 3.65                            |
| <b>35 Vdc (44 Vdc Surge)</b> |                        |                                            |      |                                              |       |                                        |
| 880                          | 325881U035GE1          | 124.0                                      | 35.0 | 2.88                                         | 5.41  | 0.77 X 1.15                            |
| 1100                         | 325112U035HE1          | 85.6                                       | 26.0 | 3.79                                         | 6.89  | 0.89 X 1.15                            |
| 1500                         | 325152U035GJ1          | 66.6                                       | 23.5 | 4.51                                         | 7.59  | 0.77 X 1.65                            |
| 1700                         | 325172U035JE1          | 63.8                                       | 17.2 | 4.78                                         | 9.22  | 1.02 X 1.15                            |
| 2200                         | 325222U035HJ1          | 42.8                                       | 14.7 | 6.15                                         | 10.51 | 0.89 X 1.65                            |
| 2200                         | 325222U035GL1          | 45.7                                       | 16.2 | 6.08                                         | 10.21 | 0.77 X 2.15                            |
| 3000                         | 325302U035GP1          | 35.2                                       | 13.6 | 7.59                                         | 12.21 | 0.77 X 2.65                            |
| 3300                         | 325332U035HL1          | 29.7                                       | 11.0 | 8.28                                         | 13.60 | 0.89 X 2.15                            |
| 3400                         | 325342U035JJ1          | 32.4                                       | 11.1 | 7.70                                         | 13.13 | 1.02 X 1.65                            |
| 3700                         | 325372U035GS1          | 28.6                                       | 11.6 | 9.09                                         | 14.23 | 0.77 X 3.15                            |
| 4300                         | 325432U035GT1          | 24.8                                       | 10.1 | 10.41                                        | 16.28 | 0.77 X 3.65                            |
| 4400                         | 325442U035HP1          | 22.9                                       | 8.6  | 10.28                                        | 16.81 | 0.89 X 2.65                            |
| 5100                         | 325512U035JL1          | 21.9                                       | 8.7  | 10.39                                        | 16.51 | 1.02 X 2.15                            |
| 5500                         | 325552U035HS1          | 18.1                                       | 7.4  | 12.47                                        | 19.48 | 0.89 X 3.15                            |
| 6300                         | 325632U035HT1          | 14.9                                       | 6.2  | 14.59                                        | 22.60 | 0.89 X 3.65                            |
| 6800                         | 325682U035JP1          | 17.1                                       | 7.3  | 12.83                                        | 19.61 | 1.02 X 2.65                            |
| 8500                         | 325852U035JS1          | 14.3                                       | 6.3  | 15.15                                        | 22.89 | 1.02 X 3.15                            |
| 10000                        | 325103U035JT1          | 12.4                                       | 5.2  | 17.37                                        | 26.70 | 1.02 X 3.65                            |

## **Type 325/326, –55 °C to 125 °C Long-Life, Switching Power Grade Radial**

---

**Notice and Disclaimer:** All product drawings, descriptions, specifications, statements, information and data (collectively, the “Information”) in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements (“Cornell Dubilier”) has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.