



CWST wraparound repair sleeve heat shrink kit, unpressurized, for 25 to 100 mm cable diameter, 1500 mm long

- Excellent split resistance of the composite structure offers superior resistance to mechanical abuse during and after the installation
- Integrated moisture barrier completely reconstitutes the cable sheath construction

## Product Classification

|                              |                           |
|------------------------------|---------------------------|
| <b>Product Series</b>        | CWST                      |
| <b>Product Type</b>          | Heat shrink repair sleeve |
| <b>Regional Availability</b> | EMEA                      |

## Dimensions

|               |                       |
|---------------|-----------------------|
| <b>Length</b> | 1500.00 mm   59.06 in |
|---------------|-----------------------|

## Environmental Specifications

|                            |                          |
|----------------------------|--------------------------|
| <b>Environmental Space</b> | Aerial   Buried   Ducted |
|----------------------------|--------------------------|

## General Specifications

|   |   |
|---|---|
| <b>Color</b>                            | Black                                       |
| <b>Expanded Wall Thickness, minimum</b> | 1.10 mm   0.04 in                           |
| <b>Material Type</b>                    | Fiber-reinforced multi-layer sealing sleeve |
| <b>Package Quantity</b>                 | 1   |
| <b>Packaging Type</b>                   | Bag   Carton                                |
| <b>Sealant Type</b>                     | Hotmelt adhesive                            |
| <b>Single Cable Diameter, maximum</b>   | 100.00 mm   3.94 in                         |
| <b>Single Cable Diameter, minimum</b>   | 25.00 mm   0.98 in                          |

## Regulatory Compliance/Certifications

**Agency**  
RoHS 2011/65/EU

**Classification**  
Compliant

