Part Number: 0348856511
Status: Active
Overview: CMC and CMX Sealed, Hybrid, Modular Connectors
Description: .635mm, 1.50mm, Power CMX Connector, 65 Circuits, Right Wire Output, Black Coding

Series image - Reference only

Documents:
Drawing (PDF)
Datasheet (PDF)
Application Specification AS-34885-002-001 (PDF)
RoHS Certificate of Compliance (PDF)

General	
Product Family	Crimp Housings
Series	34885
Application	Automotive, Power, Wire-to-Board
Comments	Current tested on 0.85mm² wire for CTX64 and CTX150 2A for CTX64, 10A for CTX150
More Detailed Tech Information	Sealed, hybrid, high-density, a new generation of CMC, suitable for rugged, powertrain applications in transportation market
Overview	CMC and CMX Sealed, Hybrid, Modular Connectors
Product Name	CMX
UPC	889056358057
Physical	
Circuits (maximum)	65
Circuits Detail	55x0.64mm, 10x1.50mm terminals
Color - Resin	Black
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Polyester
Net Weight	40.342/g
Number of Rows	5
Packaging Type	Carton
Panel Mount	No
Pitch - Mating Interface	2.50mm, 3.70mm
Stackable	No
Temperature Range - Operating	-40° to +120°C
Electrical	
Current - Maximum per Contact	10.0A, 2.0A
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-34885-002-001
Sales Drawing	SD-34885-002-001

EU ELV
Compliant

EU RoHS
Compliant

China RoHS

REACH SVHC
Not Contained Per - D(2020)4578-DC (25 June 2020)

Halogen-Free Status
Not Relevant

For more information, please visit Contact US

China ROHS	Not Relevant
ELV	Compliant
RoHS Phthalates	Not Contained

Search Parts in this Series
34885 Series

Mates With
CMX Header 5600451201

Use With
CTX64 Female Terminal 34803 , CTX150 Female Terminal 34805 , CTX150 Plugs 643251010 , 643251023 , CMX Wire Cap 5027300001