

For more Information
please call

1-800-Belden1



Description:

The insulation is cross-linked polyethylene applied in a single extrusion. This construction has excellent thermal aging characteristics, moisture resistance, and solvent resistance. The 356-series of XL-DUR is recommended for class 130(B) as motor leads

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	18	16x30	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
XLPE - Cross Linked Polyethylene	.030

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.109 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL AWM Style:	3173
UL Rating:	600 V, 125°C
CSA Rating:	600 V, 125°C
CSA Type:	CL1251
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
35618 0015000	5,000 FT	50.000 LB	BROWN	C I U Z	#18STR XLPE 125C 600VBRN

35618 Hook-up/Lead - UL AWM Style 3173 - XL-DUR®

35618 002500	500 FT	5.500 LB	RED	F	#18 STR XLPE 125C 600V
35618 0025000	5,000 FT	50.000 LB	RED	C I U Z	#18STR XLPE 125C 600VRED
35618 0035000	5,000 FT	50.000 LB	ORANGE	C I U Z	#18STR XLPE 125C 600VORG
35618 004500	500 FT	5.500 LB	YELLOW	F	#18 STR XLPE 125C 600V
35618 0045000	5,000 FT	50.000 LB	YELLOW	C I U Z	#18STR XLPE 125C 600VYEL
35618 005500	500 FT	5.500 LB	GREEN, DARK	F	#18 STR XLPE 125C 600V
35618 0055000	5,000 FT	50.000 LB	GREEN, DARK	C I U Z	#18STRXLPE 125C 600VDGRN
35618 0065000	5,000 FT	50.000 LB	BLUE, LIGHT	C I U Z	#18STRXLPE 125C 600VLBLU
35618 0075000	5,000 FT	50.000 LB	VIOLET	C I U Z	#18STR XLPE 125C 600VVIO
35618 0085000	5,000 FT	50.000 LB	GRAY	C I U Z	#18STR XLPE 125C 600VGRY
35618 0095000	5,000 FT	50.000 LB	WHITE	C I U Z	#18STR XLPE 125C 600VWHT
35618 010500	500 FT	5.500 LB	BLACK	F	#18 STR XLPE 125C 600V
35618 0105000	5,000 FT	50.000 LB	BLACK	C I U Z	#18STR XLPE 125C 600VBLK
35618 0125000	5,000 FT	50.000 LB	PINK	C I U Z	#18STR XLPE 125C 600VPNK
35618 0135000	5,000 FT	50.000 LB	BLUE, DARK	C I U Z	#18STRXLPE 125C 600VDBLU

Notes:

C = CRATE REEL PUT-UP.

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

I = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'

U = TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10000' PER COLORCOMBINATION. (SEE TOPCOAT ADDER TABLE)

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.