



368572-6 Product Details

[Share](#) | [Print](#) | [Email](#)


✔ **Active**

[View 3D PDF](#)

Power Double-Lock Connectors

PDL 3P CAP 3.96 F/H(GWT) BLU

368572-6 ✔

TE Internal Number: 368572-6

Product Highlights [View All](#)

- Wire-to-Wire
- Applies To Wire/Cable
- Connector
- Housing
- Connector Style = Receptacle

[Pricing & Availability](#)

[Request Sample](#)

[Add to My Part List](#)

[Buy Product through Distributor](#)

Feedback

[Documents](#) | [Features](#) | [Compliance](#)

Please Note:
Use the Product Drawing for all design activity

Product Type Features

Product Type	Connector
Connector Type	Housing
Wire/Cable Type	Discrete Wire
Sealed	No

Mechanical Attachment

Mating Retention Type	Latch(ing)
-----------------------	------------

Electrical Characteristics

Operating Voltage Reference	AC
Operating Voltage (VAC)	300

Termination Features

Termination Method to Wire/Cable	Crimp
----------------------------------	-------

Body Features

Wire Type	Stranded
Mating Retention	With

Contact Features

Contact Type	Tab
Contact Layout	In-Line

Housing Features

Connector Style	Receptacle
Centerline (mm [in])	3.96 [0.156]
Housing Material	PA66
Housing Color	Blue
Mating Alignment	With
Mating Alignment Type	Polarization

Configuration Features

Number of Positions	3
Number of Rows	1
Number of Double-Lock Plates Required	1

Industry Standards

RoHS/ELV Compliance	RoHS compliant, ELV compliant
Lead Free Solder Processes	Not relevant for lead free process
RoHS/ELV Compliance History	Always was RoHS compliant
Agency/Standard	USR, CNR
UL File Number	C22.2 No. 182.3, UL 1977
UL Flammability Rating	UL 94V-0

Environmental

Operating Temperature (°C [°F])	65 [149]
---------------------------------	----------

Conditions for Usage

Applies To	Wire/Cable
Glow Wire Rating	Glow Wire
For Use With	Contacts: 177916 or 177917, Double Lock Plate 177919-1, Plug (GWT): 368571

Operation/Application

Application Use	Wire-to-Wire
Contact Transmits (Typical Application)	Signal (Data)/Power

Packaging Features

Packaging Method	Bag/Box
Packaging Quantity	200

Other

Brand	TE Connectivity
Comment	Double lock plates should certainly be used when mfging. cable assemblies.

Related Products

Not quite the product you're looking for?
[Find Similar Products](#)

[View Part in Product Feature Selector](#)

[Check for Tooling](#)

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [Global Accessibility Statement](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

